



# **History and Innovation**

The story of ECHO begins with the first-ever manual duster created by the Kioritz Corporation of Japan in 1947. This evolved to the Kioritz Corporation of America establishing a presence in Northbrook, IL in 1972 as an importer of high-performance, 2-cycle handheld products from Japan. In 1978, we were officially established under ECHO Incorporated. Soon after, the focus shifted towards engineering and manufacturing in the U.S. with initial production and assembly operations in Wheeling, IL. In 1985, we established our present-day Americas' corporate headquarters and manufacturing facility in Lake Zurich, IL.

The outdoor power equipment industry is rapidly evolving. At ECHO, we always aim to develop new technology and product that enable people to do their best work.


We've historically pushed ourselves to be at the forefront, to be proactive, and to bring new ideas to market. Like when we created the world's first mini pro saw, the world's first backpack blower, the world's first handheld blower, and also the world's first low noise backpack blower. In 2021 we are introducing the PB-9010 - a backpack blower with even more power than models that have recently debuted from ECHO or any other manufacturer on the planet. The PB-9010 is unquestionably the most powerful backpack blower in the world!

Our approach to innovation is centered around power, light weight, and greater productivity delivering excellence to our customers through time and cost savings.

As we move into another year, we remain committed to innovation design and to producing the best products for you.

# **PRODUCT ICONS**

See below for enhanced explanations of select product feature icons throughout the catalog.



Reduces starting effort by 30%



Pro use

Reduces starting effort by 75%

Siphon hose

Automotive filtration

Spring assist starter

On-board detergent tank

2-stage filtration

🕬 Low noise

Spread pattern



# **TABLE OF CONTENTS**

ECHO X Series       4         Trimmers       5         Brushcutters       9         Trimmer/Brushcutter Accessories       11         Trimmer Features/Specs       15         Brushcutter Features/Specs       16         Blowers & Accessories       17         Features/Specs       21         Chainsaws - Arborist Saws       22         Rear Handle Chainsaws       24         Features/Specs       27         Bars & Chains       29         Accessories       30
Brushcutters         9           Trimmer/Brushcutter Accessories         11           Trimmer Features/Specs         15           Brushcutter Features/Specs         16           Blowers & Accessories         17           Features/Specs         21           Chainsaws - Arborist Saws         22           Rear Handle Chainsaws         24           Features/Specs         27           Bars & Chains         29           Accessories         30
Trimmer/Brushcutter Accessories       11         Trimmer Features/Specs       15         Brushcutter Features/Specs       16         Blowers & Accessories       17         Features/Specs       21         Chainsaws - Arborist Saws       22         Rear Handle Chainsaws       24         Features/Specs       27         Bars & Chains       29         Accessories       30
Trimmer Features/Specs       15         Brushcutter Features/Specs       16         Blowers & Accessories       17         Features/Specs       21         Chainsaws - Arborist Saws       22         Rear Handle Chainsaws       24         Features/Specs       27         Bars & Chains       29         Accessories       30
Brushcutter Features/Specs       16         Blowers & Accessories       17         Features/Specs       21         Chainsaws - Arborist Saws       22         Rear Handle Chainsaws       24         Features/Specs       27         Bars & Chains       29         Accessories       30
Brushcutter Features/Specs       16         Blowers & Accessories       17         Features/Specs       21         Chainsaws - Arborist Saws       22         Rear Handle Chainsaws       24         Features/Specs       27         Bars & Chains       29         Accessories       30
Blowers & Accessories       17         Features/Specs       21         Chainsaws - Arborist Saws       22         Rear Handle Chainsaws       24         Features/Specs       27         Bars & Chains       29         Accessories       30
Features/Specs       21         Chainsaws - Arborist Saws       22         Rear Handle Chainsaws       24         Features/Specs       27         Bars & Chains       29         Accessories       30
Chainsaws - Arborist Saws       22         Rear Handle Chainsaws       24         Features/Specs       27         Bars & Chains       29         Accessories       30
Rear Handle Chainsaws       24         Features/Specs       27         Bars & Chains       29         Accessories       30
Bars & Chains.       29         Accessories       30
Bars & Chains.       29         Accessories       30
Accessories
Power Pruners® & Accessories
Features/Specs
Cut-Off Saw & Accessories/Specs
Edgers & Accessories
Features/Specs
Bed Redefiner & Accessories/Specs
Hedge Trimmers
Accessories
Features/Specs
Pro Attachment Series <sup>™</sup>
Accessories
Features/Specs
Sprayers & Accessories
Features/Specs
Generators
Accessories
Features/Specs
Pressure Washers
Accessories
Features/Specs
<b>58V Cordless</b>
Engine Drill, Earth/Ice Auger, Tiller/Cultivator & Accessories 58
Features/Specs
Spreaders
Hand Tools
Wheeled Trimmers - NEW
Fire Pump - NEW
Chipper/Shredders - NEW. 67
Chipper/Shredder Accessories
Red Armor®70
Oil and Lubricant
VII AIIA MANITALIE
YouCan <sup>™</sup> Maintenance Kits



# What does it mean to be an X Series Product?

ECHO X Series models are powerful, light weight and offer greater productivity. Our goal is to give professional users strength and performance to get every job done quickly and efficiently.

We continually strive to further expand our X Series with exclusive features and innovations.





Performance. What else needs to be said about the world's finest commercial-grade grass trimmers? ECHO's easy-to-use custom ergonomic controls, lightweight design, and powerful professional-grade, 2-stroke engine technologies give you the tools to enhance your productivity. Whether you need a lightweight curved shaft model for simple trimming around posts or fence lines or you require the long reach of a straight shaft model, ECHO string trimmers are designed for performance.



# SUGGESTED TRIMMER APPLICATION



LIGHT TRIMMING MEDIUM TRIMMING HEAVY TRIMMING



A lightweight model for quick trimming tasks around the house.

- 2-line Rapid Loader® head makes line changes lightning fast
- Ergonomic adjustable handle for a custom fit
- Vibration reduction system for increased comfort
- · Curved shaft for easy maneuverability

Engine CC 21.	2
Weight (lbs) 10.	1
Shaft Length (in.)4	8
Fuel Capacity (fl. oz.)14.	2
Cutting Head:Rapid Loade	®
Cutting Swath (in.)1	6

Features i-75<sup>™</sup> for reduced starting effort ideal for quick trimming tasks around the house.

- 2-line Rapid Loader® head makes line changes lightning fast
- Ergonomic adjustable handle for a custom fit
- Vibration reduction system for increased comfort
- · Curved shaft for easy maneuverability

Engine CC	. 21.2
Weight (lbs)	. 10.6
Shaft Length (in.)	48
Fuel Capacity (fl. oz.)	. 14.2
Cutting Head:Rapid Lo	ader®
Cutting Swath (in.)	16



#### Easy-to-use residential model.

- Speed-Feed® 400 head reloads in seconds without disassembly
- · Ergonomic adjustable handle for a custom fit
- · Vibration reduction system for increased comfort
- · Curved shaft for easy maneuverability

Engine CC 21.2	
Weight (lbs) 10.8	
Shaft Length (in.)48	
Fuel Capacity (fl. oz.)14.2	
Cutting Head: Speed-Feed® 400	
Cutting Swath (in.) 16	

Extended shaft length provides longer reach for residential yard touch-ups.

- Speed-Feed® 400 head reloads in seconds without disassembly
- · Rubber overmolded throttle handle provides an ergonomic grip
- · Vibration reduction system for increased comfort
- · Extended length shaft provides more reach for increased comfort

Engine CC	2
Weight (lbs) 11.2	2
Shaft Length (in.)55	5
Fuel Capacity (fl. oz.)14.2	2
Cutting Head: Speed-Feed® 400	0
Cutting Swath (in.)10	6

STRAIGHT SHAFT



Reliable straight shaft trimmer great for light to medium applications.

- Speed-Feed® 400 head reloads in seconds without disassembly
- · Tool-less, easy-access, commercial-grade felt air filter for durability
- · Vibration reduction system for increased comfort
- · Straight shaft provides a long reach

Engine CC21	.2
Weight (lbs) 11	.7
Shaft Length (in.).	59
Fuel Capacity (fl. oz.)14	.2
Cutting Head: Speed-Feed® 46	00
Cutting Swath (in.)	17





A reliable straight shaft trimmer great for light to medium applications featuring i-75™ for reduced starting effort.

- Speed-Feed® 400 head reloads in seconds without disassembly
- · Tool-less, easy-access, commercial-grade felt air filter for durability
- · Vibration reduction system for increased comfort
- · Straight shaft provides a long reach

Engine CC2	21.2
Weight (lbs)	. 12
Shaft Length (in.)	. 59
Fuel Capacity (fl. oz.)1	4.2
Cutting Head: Speed-Feed®	400
Cutting Swath (in.)	. 17



# Feature-rich trimmer for professionals looking for increased cutting performance.

- Speed-Feed® 400 head reloads in seconds without disassembly
- 2:1 high-torque gear ratio to power through tough overgrown grass and weeds
- Vibration reduction system for increased comfort
- Chrome-plated cylinder for extended engine life

Engine CC	2
Weight (lbs) 12.2	2
Shaft Length (in.)59	)
Fuel Capacity (fl. oz.)14.2	2
Cutting Head: Speed-Feed® 400	)
Cutting Swath (in.)17	,



#### A mid-level straight shaft trimmer for medium trimming.

- Speed-Feed® 400 head reloads in seconds without disassembly
- Extra heavy-duty engine vibration reduction mount and rubber overmold handles for operator comfort
- Tool-less, easy-access, commercial-grade felt air filter for durability

Engine CC	25.4
Weight (lbs)	13.4
Shaft Length (in.)	59
Fuel Capacity (fl. oz.)	16.9
Cutting Head: Speed-Feed®	400
Cutting Swath (in.)	17







# STRAIGHT SHAFT TRIMMER

What the professionals use everyday for medium to heavy trimming.



- Speed-Feed® 400 head reloads in seconds without disassembly
- Tool-less, easy-access, commercial-grade felt air filter for durability
- 1.62:1 gear reduction for fast, efficient cutting
- Overmolded front and rear hand grips for extreme comfort

Engine CC29	5.4
Weight (lbs) 12	2.3
Shaft Length (in.)	59
Fuel Capacity (fl. oz.)20	0.6
Cutting Head: Speed-Feed® 4	00
Cutting Swath (in.)	17





## STRAIGHT SHAFT TRIMMER

A high torque version of the SRM-2620 for even greater productivity.



- Speed-Feed® 400 head reloads in seconds without disassembly
- Tool-less, easy-access, commercial-grade felt air filter for durability
- 2:1 high-torque gear ratio to power through tough overgrown grass and weeds
- Overmolded front and rear hand grips for extreme comfort



Engine CC 25.4
Weight (lbs) 12.5
Shaft Length (in.)59
Fuel Capacity (fl. oz.)20.6
Cutting Head: Speed-Feed® 400
Cutting Swath (in.)17







STRAIGHT SHAFT TRIMMER

A large displacement straight shaft model handles tough, thick grasses and weeds.



- Speed-Feed® 450 trimmer head reloads in seconds without disassembly
- Magnesium fan housing reduces weight with increased durability
- · 1.62:1 gear reduction for fast, efficient cutting
- Overmolded front and rear hand grips for extreme comfort

Engine CC3	0.5
Weight (lbs) 1	
Shaft Length (in.)	
Fuel Capacity (fl. oz.)	
Cutting Head: Speed-Feed® 4	<b>450</b>
Cutting Swath (in.)	. 20





A high torque version of the SRM-3020 for even greater productivity.







- Speed-Feed<sup>®</sup> 450 trimmer head reloads in seconds without disassembly
- Magnesium fan housing reduces weight with increased durability
- 2:1 high-torque gear ratio to power through tough overgrown grass and weeds
- Overmolded front and rear hand grips for extreme comfort

Engine CC 30.5	
Weight (lbs) 13.9	
Shaft Length (in.)59	
Fuel Capacity (fl. oz.)24	
Cutting Head: Speed-Feed® 450	
Cutting Swath (in.)20	

# SRM-410X STRAIGHT SHAFT TRIMMER

#### ECHO's most powerful trimmer.

- Speed-Feed® 450 trimmer head reloads in seconds without disassembly
- Solid steel drive shaft for smooth acceleration
- Pleated paper air filter for use in harsh conditions
- Equipped for use with a blade (blade sold separately)
- · 2-in-1 shield

Engine CC	42.7
Weight (lbs)	18.4
Shaft Length (in.)	60.2
Fuel Capacity (fl. oz.)	33.8
Cutting Head: Speed-Feed®	450
Cutting Swath (in.)	20



Power, comfort and stability is what you can expect from ECHO's brushcutters. Easy-to-use custom ergonomic controls, lightweight design, and powerful professional-grade, 2-stroke engine technologies give you the tools to enhance your productivity. Ergonomic u-handles provide improved control to tackle all clearing applications including rough grass, thickets, shrubs and dense undergrowth.



# **SUGGESTED BRUSHCUTTER APPLICATION**





blade incuded.

Features an offset handle for increased control clearing light saplings and brush.

- Offset U-handle with stop switch and throttle lock out
- Speed-Feed® 400 trimmer head reloads in seconds without disassembly
- Vibration reduction system for increased comfort
- Includes shoulder harness and 8 in.
   8-tooth brush blade

Engine CC	21.2
Weight (lbs)	13.6
Shaft Length (in.)	59
Fuel Capacity (fl. oz.)	14.2
Cutting Head: Speed-Feed®	400
Cutting Swath (in.)	17





### **U-HANDLE BRUSHCUTTER**

Increased power for professional-level brushcutting and clearing.



- · Ergonomic U-handle that folds parallel to shaft for easy transport and storage
- Speed-Feed® 400 head reloads in seconds without disassembly
- Tool-less access, two-stage air filtration system dramatically increases ease of maintenance
- · 1.62:1 gear reduction for fast, efficient cutting

Engine CC	4
Weight (lbs) 13.	3
Shaft Length (in.)5	9
Fuel Capacity (fl. oz.)20.	6
Cutting Head: Speed-Feed® 40	0
Cutting Swath (in.)1	7





Professional power for extreme clearing.





- · Ergonomic U-handle that folds parallel to shaft for easy transport and storage
- Speed-Feed® 450 head reloads in seconds without disassembly
- · Blade-ready for cattails and saplings
- · 1.62:1 gear reduction for fast, efficient cutting

1	

Engine CC	5
Weight (lbs) 14.8	
Shaft Length (in.)59	•
Fuel Capacity (fl. oz.)24	1
Cutting Head: Speed-Feed® 450	)
Cutting Swath (in.)20	)



ECHO's most powerful brushcutter equipped to clear small bushes and small trees.

- Offset U-handle with stop switch and throttle lock-out
- 10 in. 80-tooth brush blade and metal shield
- · Solid steel drive shaft for smooth acceleration and light weight

Engine CC	42.7
Weight (lbs)	19.1
Shaft Length (in.)	60.2
Fuel Capacity (fl. oz.)	33.8
Cutting Head:10" B	Blade
Cutting Swath (in.)	10

# WEGHO! TRIMMER ACCESSORIES

# **Edger Attachment**

Fits SRM-266, SRM-2620/T, and BRD-2620.

Part#: 99944230001

#### **RED ARMOR® OIL**

2-stroke semi-synthetic engine oil formulated with powerful detergents and antioxidants to clean existing deposits, protect against future carbon build-up and promote longer engine life.

Part #: 6550000
Part #: 6550001
Part #: 6550002
Part #: 6550025
Part #: 6550005
Part #: 6550006
Part #: 6550050
Part #: 6550250
Part #: 6552750

6550000	2.6 fl. oz.
: 6550001	2.6 fl. oz.
6550002	5.2 fl. oz.
6550025	6.4 fl. oz.
6550005	12.8 fl. oz
: 6550006	16 fl. oz.
6550050	1 gallon
: 6550250	5 gallons
6552750	55 gallon

ıy	48 loos
	(8) 6 pk
	(8) 6 pk
	(8) 6 pk
	12 per
	12 per
	4 per c
	1 pail

,	3 -
48 loose	1 gallon mix
(8) 6 pks.	1 gallon mix
(8) 6 pks.	2 gallon mix
(8) 6 pks.	2.5 gallon mix
12 per case	5 gallon mix
12 per case	6 gallon mix
4 per case	50 gallon mix
1 pail	250 gallon mix
1 drum	2,750 gallon mix





Our easy-to-use and innovative Speed-Feed® trimmer heads take the hassle out of refilling your trimmer head.

- · No disassembly required
- · Reload your trimmer line in 30 seconds or less
- · Rugged head for medium and heavy-duty applications
- Smooth bottom enables the head to glide along the ground for an even cut

## **EASY AS**







1 LINE UP ARROWS

2 FEED LINE

3 - TWIST BOTTOM



Scan this QR code with a smart device to see how to load trimmer line in your Speed-Feed® trimmer head.



## SPEED-FEED® 400 TRIMMER HEAD

Part #: 99944200907 - Universal fit for ECHO curved shaft and straight shaft trimmers as well as select competitor models

Part #: 999944200907B - Fits ECHO straight shaft trimmers, bulk Pkg of 24

Part #: 999444200908 - Fits ECHO curved shaft trimmers.



### SPEED-FEED® 450 TRIMMER HEAD

Part #: 99944200903 - Fits ECHO straight shaft trimmers.

## ECHOmatic® Heads

Proven economical bump head design great for mowing and trimming.

ECHOmatic® (universal) Bulk package of 24	21560070 21560070B	
ECHOmatic® Pro Bulk Package of 8	21560031 21560031B	

#### Rapid Loader® Heads

For smaller jobs with minimal obstacles. Easy to reload with pre-cut strips.

2-Line (universal) Bulk package of 24	21560056 21560056B	
2-Line (universal)	21560062	
3-Line (50% more cutting ability)	99944200221	

#### High-Capacity Manual Head

Traditional style head designed for rugged use with a large line holding capacity.

Universal	21560065	
Bulk package of 24	21560065B	

#### Heavy-Duty Fixed Line Heads

Durable aluminum head that is designed for tough cutting environments and areas that are abrasive.

Heavy-Duty	99944200220	
Heavy-Duty (High Torque)	99944200225	

#### Maxi-Cut™ Heads

For use where traditional trimmer line is not effective.

Maxi-Cut	215311 Curved Shaft	
Pro Maxi-Cut	215511 Straight Shaft	
Maxi-Cut Blades Pack of 10	215712	

# **TRIMMER LINE**



#### **BLACK DIAMOND®: TWISTED, SQUARE EDGES Small Clam** Large Clam Medium Spool Large Spool **Extra Large Spool** Line Dia. Length Length Length Length Length Length Part # Part # Part # Part # Part # Part # (in.) (ft.) (ft.) (ft.) (ft.) (ft.) (ft.) .095 253 330095071 885 330095073 1,394 330095075 217 708 330105073 .105 330105071 1,132 330105075



CR	CROSS-FIRE®: MULTI-SIDED											
Line	e Mini Clam		Small Clam		Large Clam		Medium Spool		Large Spool		Extra Large Spool	
Dia. (in.)	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #
.065	40	102152652	305	306065051	-	-	-	-	-	-	-	-
.080	40	102152802	201	306080052	402	311080062	1,206	314080052	2,010	316080052	-	-
.095	40	102152952	141	306095053	282	311095063	846	314095053	1,410	316095053	2,820	317095010
.105	-	-	117	306105055	234	311105065	702	314105055	1,170	316105055	2,340	317105010
.130	-	-	-	-	150	311130064	450	314130054	750	316130054	1,500	317130010
.155	-	-	-	-	126	311155066	378	314155056	630	316155056	1,260	317155010

PRE-CUT CROSS-FIRE® LINE FOR RAPID LOADER®										
	10	Count	20	Count	50 Count					
Line Dia. (in.)	Length (in.)	Part #	Length (in.)	Part #	Length (in.)	Part #				
.080	8	102202953	-	-	-	-				
.095	-	-	-	-	8	102222952				
.105	8	102202105	-	-	8	102222105				
.130	8	102202130	8	102212130	8	102222130				
.155	8	102202155	-	-	8	102222155				



RO	ROUND LINE										
Line	Mini Clam		Small Clam		Large Clam		Medium Spool		Large Spool		
Dia. (in.)	Length (ft.)	Part #									
.080	40	102142802	201	305080052	402	310080062	1,206	313080052	2,010	315080052	
.095	-	-	141	305095053	282	310095063	846	313095053	1,410	315095053	
.105	-	-	117	305105055	234	310105065	702	313105055	1,170	315105055	
.130	-	-	-	-	150	310130064	450	313130054	750	315130054	



SIL	SILENTWIST®: TWISTED, CURVED EDGES										
Line	Mini Clam		Small Clam		Large Clam		Medium Spool		Large Spool		
Dia. (in.)	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #	
.080	40	320080060	160	321080060	320	322080060	-	-	1,600	324080060	
.095	40	320095060	115	321095060	230	322095060	685	323095060	1,140	324095060	
.105	40	320105060	90	321105060	185	322105060	550	323105060	920	324105060	

LIGHT GRASS/WEEDS SMALL RESIDENTIAL AREAS .065" - .080" LINE MEDIUM GRASS/WEEDS LARGER RESIDENTIAL AREAS OR LIGHT COMMERCIAL AREAS .095" - .105" LINE HEAVY GRASS/WEEDS INDUSTRIAL LANDSCAPING, COMMERCIAL LANDSCAPING .130" + LINE

# TRIMMER/BRUSHCUTTER HEADS

TRIMMERS   21560062	Model	ECHOmatic <sup>®</sup>	ECHOmatic <sup>®</sup> Pro <sup>™</sup>	Heavy-Duty Fixed	Heavy- Duty Fixed (High Torque)	Speed-Feed® 400	Speed-Feed® 450	High- Capacity Manual	2-Line Rapid Loader <sup>®</sup>	3-Line Rapid Loader*	Maxi-Cut <sup>™</sup>	Pro Maxi-Cut™
Std. Line   Diameter	Part#	21560070	21560031	99944200220	99944200225		99944200903	21560065	21560056 21560062	99944200221	215311	215511
Diameter   .095 in.   .095 in.   .130"   .130"   .130"   .095 in.   .095 in	TRIMMERS											
Accepted 20 ft. 25 ft. 16 in. Strips 16 in. Strips (30 ft. GT) 25 ft. 40 ft. 8 in. Strips 8 in. Strips - Min. Line Diameter		.095 in.	.095 in.	.130"	.130"		.095 in.	.095 in.	.095 in.	.095 in.	-	-
Diameter   .080 in.		20 ft.	25 ft.	16 in. Strips	16 in. Strips		25 ft.	40 ft.	8 in. Strips	8 in. Strips	-	-
Diameter   105 in   130 in		.080 in.	.080 in.	130"	130"	.080 in.	.080 in.	.080 in.	.080 in.	.095" in.	-	-
Line		.105 in.	.130 in.	130"	130"		.130 in.	.130 in.		.155 in.	-	-
CST-58V2AHCV GT-225 GT-225I GT-225I GT-225SF GT-225L G		Cross-Fire®	Cross-Fire®	Round	Round	Cross-Fire®	Cross-Fire®	Cross-Fire®	Cross-Fire®	Cross-Fire®		Maxi-Cut Blades
GT-225	CDST-58V2AH											
GT-225I	CST-58V2AHCV											
GT-225SF	GT-225					0			0		0	
GT-225L	GT-225i					0			0			
SRM-225	GT-225SF					0			0			
SRM-225i	GT-225L					0			0			
SRM-2320T	SRM-225	0	0	0		0			0			0
SRM-266	SRM-225i	0	0	0		0			0			0
SRM-2620	SRM-2320T	0	0		0				0	0		0
SRM-2620T	SRM-266	0	0	0		0	0	0	0	0		0
SRM-3020	SRM-2620	0	0	0		D	0	0	0	0		0
SRM-3020T	SRM-2620T	0	0			0	0	0	0	0		0
SRM-410X	SRM-3020	0	0	0		0	0	0	0	0		0
BRUSHCUTTERS           SRM-225U         0         0*         0         <	SRM-3020T	0	0			0	0	0	0	0		0
SRM-225U         []         []*         []         []           SRM-2620U         []	SRM-410X			0			D	0	0	0		0
SRM-2620U [] [] [] [] [] [] [] []	BRUSHCUTTE	RS										
	SRM-225U			0		*			0			
SRM-3020U [	SRM-2620U	0	0	0		0	0	0	0	0		0
	SRM-3020U	0		0					0	0		0

Standard [] Optional []
\*Also includes 8 in. 8-tooth brush blade

# **BLADES AND CONVERSION KITS**

A variety of brush and dense grass blades are available for all ECHO straight shaft (SRM series) trimmers and brushcutters. A blade conversion kit is required if not supplied with your original trimmer. Refer to your operator's manual for the appropriate safety harnesses, handles, shields, etc. when installing optional blades or accessories.

Model		10" 3-Tooth Grass and Weed Blade		Tooth Weed Blade	8" 22- Brush		8" 80-Tooth Brush Blade		10" 80-Tooth Brush Blade
Woder	20 mm Arbor 99944200047	25 mm Arbor 99944200048	20 mm Arbor 69600120331	25 mm Arbor 69600121431	20 mm Arbor 99944200131	25 mm Arbor 99944200141	20 mm Arbor 69500120331	25 mm Arbor 69500121432	25 mm Arbor 69500121431
TRIMMERS: (*U-HANDLE KIT OR BARRIER BAR IS REQUIRED FOR ALL METAL BLADES)									
SRM-225/i		-		-	0	-	0	-	-
SRM-2320T		-		-		-	0	-	-
SRM-2620/T*		-		-		-	0	-	-
SRM-266		-		-	0	-	0	-	-
SRM-3020/T*		-	-	-	-	-	-	-	-
SRM-410X	0	-	-	-	-	-			
FOR BRUSHCU	JTTERS:								
SRM-225U		-		-	0	-	0	-	-
SRM-2620U	-	0	-	0	-	0	-		
SRM-3020U	-		-	-	-	-	-	-	
SRM-410U	-		-	-	-	-	-	-	

Standard [ Optional [ \*Please note if using a blade conversion kit, you MUST use a 20 mm blade. All blade conversion kits have 20 mm arbors.

Blade conversion kit is required for metal blades.

## **APPLICATION GUIDE:**

Small Weeds			
Large Weeds			
Reeds, Bushes, Heavy Grass	0		
Bushes, Small Trees		0	



# **BRUSHCUTTER ACCESSORIES**

**Blade Protectors** 

Part#: P021016360 (8 in. diameter)

Part#: P021007470 (10 in. diameter)



#### Offset U-Handle Kits

See chart for part number.



Model	U-Handle Kit	Blade Conversion Kit (20 mm Arbor)			
		No Blade	Includes 8" - 8-Tooth Blade		
SRM-225/i/2320T	99944200435	99944200418	99944200422		
SRM-266	99944200675	99944200418	99944200422		
SRM-2620/T*	-	99944200418	99944200422		
SRM-3020/T*	-	99944200418	-		

<sup>\* 2620</sup> series requires an 8" 20 mm blade when using 9944200418 \*\* 3020 series requires a 10" 20 mm blade when using

#### **Blade Conversion Kit**

See chart for part number.



<sup>99944200418</sup> 

TRIMMERS	GT-225	GT-225i	GT-225SF	GT-225L	SRM-225	SRM-225i	SRM-2320T	SRM-266	SRM-2620	SRM-2620T	SRM-3020	SRM-3020T	SRM-410X
	G	G	G	ڻ ا	S	S	တ	S	S	S	S	S	S
Features and Benefits													
Tool-less air filter cover for easy access	•	•	•	•	•	•	•	•	•	•	•	•	
Commercial-grade felt air filtration for long engine life	•	•	•	•	•	•							
Single-stage pleated air filtration for long engine life													•
2-stage pleated air filtration for long engine life									•	•	•	•	
2-stage commercial-grade air filtration for long engine life							•	•					
i-30™ starting system for 30% starting effort reduction	•		•	•	•			•					
i-75 <sup>™</sup> starting system for 75% starting effort reduction		•				•							
Digital ignition system for easy starting	•	•	•	•	•	•	•	•	•	•	•	•	•
Purge bulb for easy starting	•	•	•	•	•	•	•	•	•	•	•	•	•
Ergonomic throttle handle with rubber grip for comfort				•	•	•	•	•	•	•	•	•	
Ergonomic, adjustable front handle for a custom fit	•	•	•	•	•	•	•	•	•	•	•	•	•
Debris shield with integrated cut-off knife for optimal line length	•	•	•	•	•	•	•	•	•	•	•	•	
2-in-1 shield with integrated cut-off knife													•
Engine vibration-reduction system for operator comfort				•	•	•							
Extra heavy-duty vibration-reduction system for operator comfort							•	•	•	•	•	•	•
Speed-Feed* 400 cutting head for easy reloading			•	•	•	•	•	•	•	•			
High-capacity Speed-Feed* 450 cutting head for more line											•	•	•
Powerhead components made from magnesium									•	•	•	•	
Dual piston ring design for long engine life									•	•	•	•	
2:1 Pro Torque™ gear case ratio for superior power/cutting							•			•		•	
Harness, barrier bar, & blade-mount hardware included													•

# **SPECIFICATIONS**

Model	Engine Disp. (cc)	Carburetor (w/Purge Pump)	Fuel Capac- ity (fl. oz.)	Shaft Length (in)	Shaft Type	Starting System	Cutting Head	Shield and Cutting Swath (in.)	Drive Shaft	Gear Ratio	Nylon Line (in. dia)	Dry Weight (lb.)*	Dry Weight (lb.)**
GT-225	21.2	Rotary	14.2	48	Curved	i-30™	Rapid Loader®	GT with 16 in. Swath	4-Layer Cable	-	.080 Cross-Fire®	10.1	9.5
GT-225i	21.2	Rotary	14.2	48	Curved	i-75™	Rapid Loader®	GT with 16 in. Swath	4-Layer Cable	-	.080 Cross-Fire®	10.6	10.0
GT-225SF	21.2	Rotary	14.2	48	Curved	i-30™	Speed-Feed® 400	GT with 16 in. Swath	4-Layer Cable	-	.080 Cross-Fire®	10.8	9.5
GT-225L	21.2	Rotary	14.2	55	Curved	i-30™	Speed-Feed® 400	GT with 16 in. Swath	4-Layer Cable	-	.080 Cross-Fire®	11.2	10.2
SRM-225	21.2	Rotary	14.2	59	Straight	i-30™	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	1.62:1	.095 Cross-Fire®	11	11.2
SRM-225i	21.2	Rotary	14.2	59	Straight	i-75™	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	1.62:1	.095 Cross-Fire®	12	11.7
SRM-2320T	21.2	Rotary	14.2	59	Straight	Standard	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	2:1	.095 Black Dia- mond®	12.2	11.7
SRM-266	25.4	Rotary	16.9	59	Straight	i-30™	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	1.4:1	.095 Black Dia- mond®	13.4	12.3
SRM-2620	25.4	Rotary	20.6	59	Straight	Standard	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	1.62:1	.095 Black Dia- mond®	12.3	11.7
SRM-2620T	25.4	Rotary	20.6	59	Straight	Standard	Speed-Feed® 400	SRM with 17 in. Swath	4-Layer Cable	2:1	.095 Black Dia- mond®	12.5	11.9
SRM-3020	30.5	Rotary	24	59	Straight	Standard	Speed-Feed® 450	SRM with 20 in. Swath	4-Layer Cable	1.62:1	.095 Black Dia- mond®	13.7	12.1
SRM-3020T	30.5	Rotary	24	59	Straight	Standard	Speed-Feed® 450	SRM with 20 in. Swath	4-Layer Cable	2:1	.095 Black Dia- mond®	13.9	12.3
SRM-410X	42.7	Rotary	33.8	60.3	Straight	Standard	Speed-Feed® 450	SRM with 20 in. Swath	Steel	1.33:1	.095 Black Dia- mond®	18.4	16.3

BRUSHCUTTERS	SRM-225U	SRM-2620U	SRM-3020U	SRM-410U
Features and Benefits				
Tool-less air filter cover for easy access	•	•	•	
Commercial-grade felt air filtration for long engine life	•			
Pleated air filtration for long engine life				•
2-stage pleated air filtration for long engine life		•	•	
i-30™ starting system for 30% starting effort reduction	•			
Digital ignition system for easy starting	•	•	•	•
Purge bulb for easy starting	•	•	•	•
Ergonomic U-handle with rubber grip for comfort and handling	•	•	•	•

# **SPECIFICATIONS**

Debris shield with integrated cut-off knife for optimal line length

Extra heavy-duty vibration-reduction system for operator comfort

High-capacity Speed-Feed® 450 cutting head for more line and larger line diameters

Powerhead components made from high-grade magnesium for light weight and durability

Engine vibration-reduction system for operator comfort

Shoulder harness included for comfort and convenience

Additional shield and hardware included for blade use

Speed-Feed® 400 cutting head for easy reloading

Dual piston ring design for long engine life

Tool-less U bar adjustment knob for ease of storage

Model	Engine Disp. (cc)	Carburetor (w/Purge Pump)	Fuel Capac- ity	Shaft Length (in)	Shaft Type	Starting System	Cutting Head	Shield and Cut- ting Swath (in.)	Drive Shaft	Arbor Size (mm)	Nylon Line (in. dia)	Dry Weight (lb.)*	Dry Weight (lb.)**
SRM-225U	21.2	Rotary	14.2	59	Straight	i-30™	Speed-Feed® 400	SRM 17 in. Swath w/ Blade Shield	4-Layer Cable	25	.095 Cross- Fire®	13.6	12.7
SRM-2620U	25.4	Rotary	20.6	59	Straight	Standard	Speed-Feed® 400	SRM 17 in. Swath w/ Blade Shield	4-Layer Cable	25	.095 Black Diamond®	13.3	12.4
SRM-3020U	30.5	Rotary	24	59	Straight	Standard	Speed-Feed® 450	SRM 20 in. Swath w/ Blade Shield	4-Layer Cable	25	.095 Black Diamond®	14.8	13.2
SRM-410U	42.7	Rotary	33.8	60.2	Straight	Standard	10 in. Brush Blade	Metal Blade Shield	Steel	25	-	19.1	18.3



ECHO's best-in-class line of blowers includes both handheld and backpack models. All come equipped with professional features to give you maximum productivity and ultimate power. Standard features include comfortable handles with "cruise control" and backpack models feature padded backrests and shoulder straps, Posi-loc™ tubes for secure pipe connections and advanced ignitions for quick and easy starts. All ECHO's backpack blowers (except the PB-265LN) are available in either tube-mounted or hip-mounted throttles.



# **SUGGESTED BLOWER APPLICATION**





# Blower and Shred 'N' Vac® Rain Gutter Kit

Provides up to 15 ft. of reach with 7 ft. of extension tubes.

Fits PB-2520, PB-255LN, PB-2620, ES-250 PB-265LN, PB-580, and PB-755S.

Part#: 99944100026 Posi-loc™



#### **Curved Tube**

Angled design allows increased control when directing air flow.
Fits PB-760LN, PB-770

Part#: E165000730

# PB-2520

#### HANDHELD BLOWER



A great performance blower at a great value - ideal for quick clean-ups around the house.

- Double-grid air intake design reduces clogging and interference with user's clothing
- Exclusive curved blower tube provides rotational control to reduce user fatigue
- Shoulder harness attachment points allow the use of shoulder harness (sold separately) to support weight of unit
- Tool-less access air filter for convenient in-field servicing

Engine CC	
Weight (lbs)	8.6
Fuel Capacity (fl. oz.)	18.6
Max Air Speed at Nozzle (mph)	170
Newton Blowing Force (N) at Nozzle	15.8
Air Volume at Nozzle (CFM)	453
Noise Level (dB(A))*	70

# **PB-255LN**

### HANDHELD BLOWER



A low-noise blower that's perfect for noise-sensitive environments.

- Low noise, 65 dB(A)\* output for noise sensitive environments
- Parallel handles aid in directional operation
- Rubber top handle grip for more comfort
- · Flared pipe for increased air speed

Engine CC	25.4
Weight (lbs)	10.2
Fuel Capacity (fl. oz.)	16.9
Max Air Speed at Nozzle (mph)	191
Newton Blowing Force (N) at Nozzle	13
Air Volume at Nozzle (CFM)	354
Noise Level (dB(A))*	65



# HANDHELD BLOWER

ECHO's best-in-class handheld blower for lightweight performance on more demanding jobs.



- Double-grid air intake design reduces clogging and interference with user's clothing
- Includes both round and flared pipes for a variety of applications
- · Rubber top handle grip for more comfort
- Secondary handle improves maneuverability and comfort

Engine CC	25.4
Weight (lbs)	
Fuel Capacity (fl. oz.)	20.3
Max Air Speed at Nozzle (mph)	172
Newton Blowing Force (N) at Nozzle	15.8
Air Volume at Nozzle (CFM)	456
Noise Level (dB(A))*	70

<sup>\*</sup>Per ANSI B175.2-2012



Ideal for residential lawn maintenance with three tools in one: a blower, a vacuum, and a shredder/mulcher.

- Patented 4-blade shredding mechanism reduces debris by a ratio of 12:1
- 2-bushel collection bag with rear zipper for convenient emptying
- Exclusive curved blower tube provides rotational control to reduce user fatigue (when set up as a blower)
- All pipes included to convert from shredder to blower

Engine CC	25.4
Weight (lbs)	12.6
Fuel Capacity (fl. oz.)	16.9
Max Air Speed at Nozzle (mph)	165
Newton Blowing Force (N) at Nozzle	12.5
Air Volume at Nozzle (CFM)	392
Noise Level (dB(A))*	70



Features a lightweight design, making this blower easy to carry for routine lawn maintenance.

- Low noise, 65 dB(A)\* output for noise sensitive environments
- Padded backrest and shoulder straps for comfort
- Variable speed throttle with cruise control for operator convenience
- · Hip-mounted throttle

\*Per ANSI B175.2-2012

Engine CC	25.4
Weight (lbs)	13.3
Fuel Capacity (fl. oz.)	22.3
Max Air Speed at Nozzle (mph)	158
Newton Blowing Force (N) at Nozzle	11
Air Volume at Nozzle (CFM)	375
Noise Level (dB(A))*	65



A blower with increased power, ideal for larger residential chores or entry-level pros.

- Available with hip- (PB-580H) or tube- (PB-580T) mounted throttle with cruise control
- Exclusive vented back pad circulates air around user for increased comfort in hot weather
- Padded backrest and shoulder straps for comfort
- Patented metal wear ring is a useful debris scraper and protects blower pipe from damage

Engine CC	58.2
Weight (lbs)2	2.9/22.7
Fuel Capacity (fl. oz.)	62
Max Air Speed at Nozzle (mph)	216
Newton Blowing Force (N) at Nozzle.	22
Air Volume at Nozzle (CFM)	517
Noise Level (dB(A))*	70



Professional, value-driven performance, great for large home plots or commercial use.

- Available with hip- (PB-755SH) or tube- (PB-755ST) mounted throttle with cruise control
- Extra flexible tube for cold weather operation
- Wide-angle tube rotation for optimum mobility
- Padded backrest and shoulder straps for comfort

Engine CC	63.3
Weight (lbs)25.	4/25.1
Fuel Capacity (fl. oz.)	67.6
Max Air Speed at Nozzle (mph)	233
Newton Blowing Force (N) at Nozzle	28
Air Volume at Nozzle (CFM)	651
Noise Level (dB(A))*	74



#### The most powerful low-noise blower available.

- · Available with hip- (PB-760LNH) or tube- (PB-760LNT) mounted throttle with cruise control
- · Low noise, 65 dB(A)\* output for noise sensitive environments
- · Exclusive vented back pad circulates air around user for increased comfort in hot weather
- · Side-mounted, heavy-duty, dual-stage air filtration for long engine life

Engine CC	. 63.3
Weight (lbs)26.5	/26.2
Fuel Capacity (fl. oz.)	. 68.3
Max Air Speed at Nozzle (mph)	214
Newton Blowing Force (N) at Nozzle	21
Air Volume at Nozzle (CFM)	535
Noise Level (dB(A))*	65

A powerful, large displacement option for professionals or properties with heavy debris.



- Available with hip- (PB-770H) or tube- (PB-770T) mounted throttle with cruise control
- Padded backrest and shoulder straps for comfort
- · Exclusive vented back pad circulates air around user for increased comfort in hot weather
- · Side-mounted, heavy-duty, dual-stage air filtration for long engine life

Engine CC	63.3
Weight (lbs)	
Fuel Capacity (fl. oz.)	68.3
Max Air Speed at Nozzle (mph)	234
Newton Blowing Force (N) at Nozzle	33
Air Volume at Nozzle (CFM)	756
Noise Level (dB(A))*	74

# **BACKPACK BLOWER**

The most powerful blower in the world that is disrupting the industry with unquestionable performance.



- Available with hip- (PB-9010H) or tube- (PB-9010T) mounted throttle with cruise control
- Exclusive vented back pad circulates air around user for increased comfort in hot weather
- · Heavy-duty padded backrest and shoulder straps for comfort

Engine CC	79.9
Weight (lbs)26	.7/26.4
Fuel Capacity (fl. oz.)	83.8
Max Air Speed at Nozzle (mph)	220
Newton Blowing Force (N) at Nozzle	48
Air Volume at Nozzle (CFM)	1,110
Noise Level (dB(A))*	80

<sup>\*</sup>Per ANSI B175.2-2012

BLOWERS	PB-2520	PB-255LN	PB-2620	PB-265LN	PB-580H	PB-580T	PB-755SH	PB-755ST	PB-760LNH	PB-760LNT	PB-770H	PB-770T	PB-9010H	PB-9010T	ES-250
Features and Benefits															
Posi-loc <sup>™</sup> pipes for a secure connection	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
i-30™ starting system for 30% starting effort reduction				•											
Padded backrest and shoulder straps for comfort				•	•	•	•	•	•	•	•	•	•	•	
Low-noise, 65 dB(A) or less, output for noise-sensitive environments		•		•					•	•					
Pleated, automotive-style air filter for superior filtration			•		•	•	•	•	•	•	•	•	•	•	
Hip-mounted throttle with cruise control				•	•		•		•		•		•		
Tube-mounted throttle with cruise control						•		•		•		•		•	
"L"-style frame for impact damage resistance				•	•	•	•	•	•	•	•	•	•	•	
Leaf guard for keeping debris out of fan intake					•	•	•	•	•	•	•	•	•	•	
Extra-flexible tube for cold weather operation				•	•	•	•	•	•	•	•	•	•	•	
Wide-angle tube rotation for optimum mobility				•	•	•	•	•	•	•	•	•	•	•	
Rotational control for reduced operator fatigue	•														•
Rubber top handle grip for comfort and control		•	•												
Parallel handles for all-position operation		•	•												•
Flared-end pipe for moving heavy or wet debris		•	•												
Throttle with cruise control for operator convenience	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Professional-grade felt air filtration for long engine life	•	•		•											•
35 in. long intake tube for easy reach															•
Patented, 4-blade shredding mechanism for optimum debris reduction															•
2-bushel collection bag with rear zipper for convenient emptying															•

# **SPECIFICATIONS**

Model	Blower Type	Engine Disp. (cc)	Carb. (Purge Pump)	Starting System	Fuel Cap. (fl. oz.)	Air Volume* (CFM-pipe)	Maximum Air Speed* (MPH-pipe)	Newtons (N)	Noise Level dB(A)	Dry Weight** (lb)
PB-2520	Handheld	25.4	Yes	Standard	18.6	453	170	15.8	70	8.6
PB-255LN	Handheld	25.4	Yes	Standard	16.9	354	191	13	65	10.2
PB-2620	Handheld	25.4	Yes	Standard	20.3	456	172	15.8	70	9.8
PB-265LN	Backpack	25.4	Yes	i-30™	22.3	375	158	11	65	13.3
PB-580H/T	Backpack	58.2	Yes	Standard	62.0	517	216	22	70	22.9/22.7
PB-755SH/T	Backpack	63.3	Yes	Standard	67.6	651	233	28	74	25.1/25.4
PB-760LNH/T	Backpack	63.3	Yes	Standard	68.3	535	214	21	65	26.5/26.2
PB-770H/T	Backpack	63.3	Yes	Standard	68.3	756	234	33	74	24.5/24.3
PB-9010H/T	Backpack	79.9	Yes	Standard	83.8	1,110	220	48	80	26.4/26.7
ES-250	Shred 'N' Vac	25.4	Yes	Standard	16.9	392	165	12.5	70	12.6

\*per ANSI B175.2-2012 \*\*with blower pipe



Backed by professionals, ECHO top and rear handle chainsaws can tackle the toughest jobs out there and will give you superior, smooth operation. Get the power and durability you need from the high-performance, 2-stroke engine and the fast start you want with our advanced ignition system. All ECHO chainsaws come standard with the best pro features such as vibration reduction systems, automatic oilers, inertia chain brakes and more.



# **SUGGESTED ARBORIST SAW APPLICATION**

Top handle saw models for use by professionals only.



CS-2511T CS-2511P CS-271T

CS-2511T CS-2511P CS-271T CS-303T CS-355T

CS-355T CS-361P



**SMALL LIMBING** 

**MEDIUM LIMBING & SECTIONING** 

**LARGE LIMBING & SECTIOING** 



The lightest gas-powered chainsaw in North America.

TOP HANDLE CHAINSAW



- Class-leading combination of light weight and high horsepower for limbing and pruning
- · Fine grid starter cover prevents debris ingestion for longer life and less maintenance
- Rear-mounted, tool-less access air filter cover for quick maintenance
- Large 1 in. fuel and oil caps, that can be removed with the starter handle, for easy filling

Engine CC29	5
Weight (lbs)5.2	2
Bar Length (in.)12, 14	4
Fuel Capacity (fl. oz.)6.4	4
Oil Capacity (fl. oz.)4.7	7









**REAR HANDLE CHAINSAW** 



#### The lightest rear handle gas-powered chainsaw in the world.

- Class-leading combination of light weight and high horsepower for low-level pruning and felling small trees
- Fine grid starter cover prevents debris ingestion for longer life and less maintenance
- · Two-piece mesh air filter for easy cleaning
- Palm rest provides a secure hand hold for more control

Engine CC25
Weight (lbs)5.7
Bar Length (in.)12, 14
Fuel Capacity (fl. oz.)6.4
Oil Capacity (fl. oz.)4.7







# **CS-271T**TOP HANDLE CHAINSAW



#### A perfect choice for light trimming and pruning.

- i-30™ starter reduces starting effort by 30%
- Rear-mounted, tool-less access air filter cover for quick maintenance
- Side-access chain tensioner for easy chain adjustments
- Purge bulb provides fresh fuel to carburetor for fast starts

Engine CC Weight (lbs) Bar Length (in.) Fuel Capacity (fl. oz.)	6.6
Oil Capacity (fl. oz.)	







# CS-303T TOP HANDLE CHAINSAW



# A proven design that works best for small to medium limbing and pruning.

- Extended handle for greater reach, maneuverability and control
- Side-access chain tensioner for easy chain adjustments
- Purge bulb provides fresh fuel to carburetor for fast starts
- · Automatic adjustable oiler to match cutting conditions

Engine CCWeight (lbs)	
Bar Length (in.)	.12, 14
Fuel Capacity (fl. oz.)	8.5
Oil Capacity (fl. oz.)	5.1



# **CS-355T**TOP HANDLE CHAINSAW



# ECHO's most powerful top handle chainsaw for heavier branches and sectioning trees.

- Contoured, ergonomic handle designed to fit your hand for great operator comfort
- · Vibration reduction system for increased comfort
- Integrated choke and fast idle with trigger release for fast starts
- Purge bulb provides fresh fuel to carburetor for fast starts

Engine CC <b>35.8</b>
Weight (lbs)8
Bar Length (in.)14, 16
Fuel Capacity (fl. oz.) 11.2
Oil Capacity (fl. oz.)8.2







# **GS-361P**REAR HANDLE CHAINSAW



# A powerful and compact chainsaw for arborists who prefer a rear handle configuration.

- Heavy-duty, tool-less, air filter for superior filtration
- · Vibration reduction system for increased comfort
- Integrated choke and fast idle with trigger release for fast starts.
- Purge bulb provides fresh fuel to carburetor for fast starts

Engine CC	35.8
Weight (lbs)	8.4
Bar Length (in.)	14, 16
Fuel Capacity (fl. oz.)	10.8
Oil Capacity (fl. oz.)	7.8





# **SUGGESTED REAR HANDLE CHAINSAW APPLICATION**





**TRIMMING & LIMBING** 

TREE FELLING

LARGE TREE FELLING

# **CS-310** REAR HANDLE CHAINSAW



An entry-level chainsaw for general yard clean-up, small tree felling and light pruning.

- i-30™ starter reduces starting effort by 30%
- Top-mounted, tool-less access air filter cover for quick maintenance
- · Vibration reduction system for increased comfort
- Side-access chain tensioner for easy chain adjustments

Engine CC	30.5
Weight (lbs)	8.8
Bar Length (in.)	.14, 16
Fuel Capacity (fl. oz.)	8.5
Oil Capacity (fl. oz.)	8.8







# CS-3510 REAR HANDLE CHAINSAW



The lightest chainsaw in its class, ideal for yard or storm clean-up and small to medium tree felling.

- i-30™ starter reduces starting effort by 30%
- Multiple-stage air filtration system cleans air and reduces air filter maintenance
- Momentary stop switch automatically returns to on position
- · Translucent fuel tank for quick fuel level checks

Engine CC	34.4
Weight (lbs)	8.2
Bar Length (in.)	16
Fuel Capacity (fl. oz.)	9.5
Oil Capacity (fl. oz.)	7.8





# CS-400 REAR HANDLE CHAINSAW



A perfect chainsaw for cutting firewood and storm clean-up.

- i-30™ starter reduces starting effort by 30%
- Heavy-duty, tool-less, easy-access, automotive-style air filter for superior filtration
- Side-access chain tensioner for easy chain adjustments

Engine CC	10.1 .16, 18 13.9
-----------	-------------------------







# CS-4510 REAR HANDLE CHAINSAW



An easy-to-start and operate chainsaw for mid-range and larger jobs.

- · Spring-assist starter reduces starting effort
- Multiple-stage air filtration system cleans air and reduces air filter maintenance
- Momentary stop switch automatically returns to on position
- · Translucent fuel tank for guick fuel level checks

Engine CC45
Weight (lbs)11.1
Bar Length (in.) <b>16, 18</b>
Fuel Capacity (fl. oz.)16.2
Oil Capacity (fl. oz.) 11.1







# NEW CS-4910 REAR HANDLE CHAINSAW



A lightweight and powerful chainsaw for heavier jobs, such as installing fence posts, storm clean-up and firewood cutting.

- · Decompression valve for easier starting
- Heavy-duty, easy-access air filter for convenient in-field servicing
- · Magnesium crankcase is lightweight and durable







A great chainsaw for everyday use on larger jobs and heavy on-ground use.

- · Decompression valve for easier starting
- Ergonomic aluminum front handle with rubber grip for improved comfort and maneuverability
- · Two-piece flocked air filter for easy cleaning
- Captive bar nuts eliminates chance of losing fasteners

Engine CC	50.2
Weight (lbs)	10.4
Bar Length (in.)	.18, 20
Fuel Capacity (fl. oz.)	16.6
Oil Capacity (fl. oz.)	9.5





# CS-590 TIMBER REAR HANDLE CHAINSAW



The perfect chainsaw for farm/ranch use or larger land lots and tree felling.

- · Decompression valve for easier starting
- Heavy-duty, easy-access air filter for convenient in-field servicing
- · Two-piece flocked air filter for easy cleaning
- · Translucent fuel tank for quick fuel level checks

Engine CC <b>59.8</b>	
Weight (lbs)13.2	
Bar Length (in.)18, 20, 24	
Fuel Capacity (fl. oz.)21.8	
Oil Capacity (fl. oz.) 10.2	
on capacity (iii 62.)	







**REAR HANDLE CHAINSAW** 



A powerful chainsaw ideal for heavy on-ground use, logging and larger clearing jobs.

- Decompression valve for easier starting
- Heavy-duty, easy-access air filter for convenient in-field servicing
- Heavy-duty aluminum handle with rubber grip for increased comfort and reduced vibration
- Professional-grade magnesium sprocket cover and crank case







**REAR HANDLE CHAINSAW** 



A powerful chainsaw with a full-wrap handle ideal for heavy on-ground use, logging and larger clearing jobs.

- · Decompression valve for easier starting
- Heavy-duty, easy-access air filter for convenient in-field servicing
- Heavy-duty full-wrap aluminum handle with rubber grip for more gripping options and reduced vibration
- Professional-grade magnesium sprocket cover and crank case

Engine CC	59.8
Weight (lbs)	
Bar Len. (in.)	20, 24, 27
Fuel Capacity (fl. oz.)	21.8
Oil Capacity (fl. oz.)	10.2





# **CS-680**REAR HANDLE CHAINSAW



#### A great choice for tree felling.

- Top-mounted, tool-less access air filter cover for quick maintenance
- Heavy-duty, easy-access, automotive-style air filter extends saw life
- Aluminum handle with rubber overmold for improved comfort
- Side-access chain tensioner for easy chain adjustment

Engine CC <b>66.8</b>
Weight (lbs)14.6
Bar Length (in.)20, 24, 27
Fuel Capacity (fl. oz.)21.6
Oil Capacity (fl. oz.)12.5





# NEW CS-7310P REAR HANDLE CHAINSAW



# The most powerful ECHO chainsaw available in North America.

- Multiple-stage air filtration system cleans air and reduces air filter maintenance
- Heavy-duty aluminum handle with rubber grip for increased comfort and reduced vibration
- Professional-grade magnesium sprocket cover, starter cover, and crank case
- · Translucent fuel tank for quick fuel level checks

Engine CC73	3.5
Weight (lbs)14	l.9
Bar Length (in.)20, 24, 28,	32
Fuel Capacity (fl. oz.)27	<b>'.1</b>
Oil Capacity (fl. oz.)12	2.2





ARBORIST CHAINSAWS	CS-2511T	CS-2511P	CS-271T	CS-303T	CS-355T	CS-361P
Features and Benefits						
Dual-post chain brake for extra durability	•	•			•	
Inertia-type chain brake for safety	•	•	•	•	•	•
Tool-less air filter cover for easy access			•			•
Tall profile bar with multi-rivet nose for longer life					•	•
Premium chain with extended-length cutters for greater life	•	•			•	•
Vibration-reduction system for operator comfort	•	•	•	•	•	•
i-30™ starting system for 30% starting effort reduction			•			
Spring-assisted starting system for reduced effort starting	•	•			•	•
Digital ignition system for easy starting and smooth acceleration	•	•	•		•	•
Integrated choke and fast idle with trigger release for easy starting	•	•	•		•	•
G-Force Engine Air Pre-Cleaner™ for cleaner air supply to engine	•	•	•		•	•
Automatic, adjustable oiler to match cutting conditions				•		
Automatic, adjustable clutch-driven oiler for reduced oil consumption	•	•	•		•	•
Replaceable, metal bumper spike for improved control		•			•	•
Side access chain tensioner for quick chain adjustments	•	•	•	•	•	•
Metal lanyard ring for easy attaching and detaching to harness	•			•	•	
Optional metal bumper spike for more control	•	•	•			
Purge bulb for easy starting	•	•	•	•	•	•

# **SPECIFICATIONS**

Model	Engine Disp. (cc)	Starting System	Purge Bulb	Oiling System	Vibration Reduction	Available Bar Length (in)	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Dry Weight* (lb)
CS-2511T	25.0	Spring-Assist	Yes	Auto/Adjustable**	Yes	12, 14	6.4	4.7	5.2
CS-2511P	25.0	Spring-Assist	Yes	Auto/Adjustable**	Yes	12, 14	6.4	4.7	5.7
CS-271T	26.9	i-30™	Yes	Auto/Adjustable**	Yes	12	8.1	5.4	6.6
CS-303T	30.1	Standard	Yes	Auto/Adjustable	Yes	12 (14 U.S. only)	8.5	5.1	7.7
CS-355T	35.8	Spring-Assist	Yes	Auto/Adjustable**	Yes	14, 16	11.2	8.2	8.0
CS-361P	35.8	Spring-Assist	Yes	Auto/Adjustable**	Yes	14, 16	10.8	7.8	8.4

\*without bar and chain \*\*clutch-driven

DEAD HANDLE CHAINCAWC	CS-310	CS-3510	CS-400	CS-4510	CS-4910	CS-501P	CS-590	CS-620P	CS-620PW	CS-680	CS-7310P
REAR HANDLE CHAINSAWS	ĊS	SS	SS	ĊS	ĊS	cs	cs	SS	SS	cs	SS
Features and Benefits											
Dual-post chain brake for extra durability	•	•	•	•	•	•	•	•	•		•
Inertia-type chain brake for safety	•	•	•	•	•	•	•	•	•	•	•
Tool-less air filter cover for easy access	•		•	•	•	•	•	•	•	•	
Automotive-style air filter for superior filtration			•							•	•
Two-piece air filter for easy cleaning	•	•			•	•	•	•	•		
Round felt air filter				•							
Vibration-reduction system for operator comfort	•	•	•	•	•	•	•	•	•	•	•
i-30™ starting system for 30% starting effort reduction	•	•	•								
Spring-assisted starting system for reduced effort starting				•							
Digital ignition system for easy starting and smooth acceleration	•	•	•	•	•	•	•	•	•		•
Integrated choke and fast idle with trigger release	•	•	•	•	•	•	•	•	•		•
G-Force Engine Air Pre-Cleaner™ for cleaner air supply	•		•		•	•	•	•	•		
Multiple stage air filtration system		•		•							•
Automatic clutch-driven oiler for reduced oil usage	•	•									
Automatic, adjustable oiler to match cutting conditions			•								
Automatic, adjustable clutch-driven oiler for reduced oil usage				•	•	•	•	•	•		•
Automatic, adjustable oiler with manual override										•	
Performance Cutting System <sup>™</sup> - upgraded bar and chain						•		•	•	•	•
Replaceable, metal bumper spike for improved control			•	•	•	•	•	•	•	•	•
Side access chain tensioner for quick chain adjustment	•	•	•	•	•	•	•	•	•	•	•
Decompression valve for easy starting					•	•	•	•	•		•
Aluminum handle with rubber grip for improved comfort						•		•	•	•	•
Purge bulb for easy starting	•	•	•	•							
Wrap handle for more gripping options									•		
Translucent fuel tank for easy level checks		•		•	•	•	•	•	•		•

# **SPECIFICATIONS**

Model	Engine Disp. (cc)	Starting System	Purge Bulb	Oiling System	Vibration Reduction	Available Bar Length (in)	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Dry Weight* (lb)
CS-310	30.5	i-30™	Yes	Automatic**	Yes	14, 16	8.5	8.8	8.8
CS-3510	34.4	i-30™	Yes	Automatic**	Yes	16	9.5	7.8	8.2
CS-400	40.2	i-30™	Yes	Auto/Adjustable	Yes	16, 18	13.9	9.5	10.1
CS-4510	45.0	Spring-Assist	Yes	Auto/Adjustable**	Yes	16, 18	16.2	11.1	11.1
CS-4910	50.2	Standard	No	Auto/Adjustable**	Yes	16, 18, 20	16.6	9.5	10.4
CS-501P	50.2	Standard	No	Auto/Adjustable**	Yes	16 (+), 18, 20	16.6	9.5	10.4
CS-590	59.8	Standard	No	Auto/Adjustable**	Yes	18, 20, 24	21.8	10.2	13.2
CS-620P/PW	59.8	Standard	No	Auto/Adjustable**	Yes	16 (+), 18 (+ 620PW), 20, 24, 27	21.8	10.2	13.7/14.1
CS-680	66.8	Standard	No	Auto/Adjustable***	Yes	20, 24, 27	21.6	12.5	14.6
CS-7310P	73.5	Standard	No	Auto/Adjustable***	Yes	20, 24, 28, 32	27.1	12.2	14.9

(+) Bar lengths available as accessories only  $\,\,$  \*without bar and chain  $\,\,$  \*\*clutch-driven  $\,\,$  \*\*\*with manual override

# **BARS AND CHAINS**

		BAR					CHAIN		
Chainsaw Models	Length in. (cm)	Sprocket Nose	Bar Part #	Drive Link Count	Gauge (in.)	Pitch (in.)	Chain Part#	File Size (in.)	3-pack Chain
	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PXL45CQ	5/32	-
CS-2511P	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PXL52CQ	5/32	-
	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PXL45CQ	5/32	-
CS-2511T	12 (30)	Non-Replaceable	12A4CD3745C	45	.043	3/8 lp	90PX45CQ	4.5 mm	-
	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PXL52CQ	5/32	-
	14 (35)	Non-Replaceable	14A4CD3752C	52	.043	3/8 lp	90PX52CQ	4.5 mm	-
CS-271T	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PX45CQ	5/32	-
	12 (30)	Non-Replaceable	12A4CD3745C	45	.043	3/8 lp	90PX45CQ	4.5 mm	-
	12 (30)	Non-Replaceable	12A0CD3745C	45	.050	3/8 lp	91PX45CQ	5/32	-
CS-303T/310	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PX52CQ	5/32	91PX52CQ-3
	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32	91PX57CQ-3
CS-355T	12 (30)	Non-Replaceable	12A0ED3745C	45	.050	3/8 lp	91PX45CQ	5/32	-
00.0557/0045	14 (35)	Non-Replaceable	14A0ES3752C	52	.050	3/8 lp	91PXL52CQ	5/32	-
CS-355T/361P	16 (40)	Non-Replaceable	16A0ES3757C	57	.050	3/8 lp	91PXL57CQ	5/32	-
	14 (35)	Non-Replaceable	14A0CD3752C	52	.050	3/8 lp	91PX52CQ	5/32	91PX52CQ-3
CS-3510	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32	91PX57CQ-3
	16 (40)	Non-Replaceable	16A0CD3757C	57	.050	3/8 lp	91PX57CQ	5/32	91PX57CQ-3
CS-400	18 (45)	Non-Replaceable	18A0CD3762C	62	.050	3/8 lp	91PX62CQ	5/32	91PX62CQ-3
	16 (40)	Non-Replaceable	16B0AD3366C	66	.050	.325	20BPX66CQ	3/16	-
CS-4510	18 (45)	Non-Replaceable	18B0AD3372C	72	.050	.325	20BPX72CQ	3/16	_
	20 (50)	Non-Replaceable	20B0AD3378C	78	.050	.325	20BPX78CQ	3/16	_
	16 (40)	Non-Replaceable	16F0AD3366C	66	.050	0.325	20BPX66CQ	3/16	_
CS-4910	18 (45)	Non-Replaceable	18F0AD3372C	72	.050	0.325	20BPX72CQ	3/16	_
	20 (50)	Non-Replaceable	20F0AD3378C	78	.050	0.325	20BPX78CQ	3/16	_
	16 (40)	Non-Replaceable	16F0LD3366C	66	.050	.325	20LPX66CQ	3/16	-
CS-501P	18 (45)	Non-Replaceable	18F0LD3372C	72	.050	.325	20LPX72CQ	3/16	_
	20 (50)	Non-Replaceable	20F0LD3378C	78	.050	.325	20LPX78CQ	3/16	_
	18 (45)	Non-Replaceable	18D0AS3864C	64	.050	3/8	72LPX64CQ	7/32	_
	20 (50)	Non-Replaceable	20D0AS3870C	70	.050	3/8	72LPX70CQ	7/32	72LPX70CQ-3
CS-590	24 (60)	Non-Replaceable	24D0AS3884C	84	.050	3/8	72LPX84CQ	7/32	_
	24 (60)	Replaceable	24D0PS3881C*	81	.050	3/8	72LPX81CQ	7/32	_
	16 (40)	Replaceable	16D0PS3860C*	60	.050	3/8	72LPX60CQ	7/32	_
	18 (45)	Replaceable	18D0PS3866C*	66	.050	3/8	72LPX66CQ	7/32	_
CS-	20 (50)	Replaceable	20D0PS3870C*	70	.050	3/8	72LPX70CQ	7/32	72LPX70CQ-3
620P/620PW/680	24 (60)	Replaceable	24D0PS3881C*	81	.050	3/8	72LPX81CQ	7/32	-
	27 (68)	Replaceable	27D0PS3893C*	93	.050	3/8	72LPX93CQ	7/32	_
	20 (50)	Replaceable	20H0PS3872C*	72	.050	3/8	72LPX72CQ	7/32	_
	20 (50)	Replaceable	20H8PS3872C*	72	.058	3/8	73LPX72CQ	7/32	
	24 (60)	Replaceable	24H0PS3884C*	84	.050	3/8	72LPX84CQ	7/32	
	24 (60)	Replaceable	24H8PS3884C*	84	.058	3/8	73LPX84CQ	7/32	
CS-7310P	28 (70)	Replaceable	28H0PS3893C*	93	.050	3/8	73LPX84CQ 72LPX93CQ	7/32	
	28 (70)	·	28H8PS3892C*	92	.050	3/8	73LPX93CQ	7/32	-
		Replaceable							
	32 (80)	Replaceable Replaceable	32H0PS3805C*	105	.050 .058	3/8 3/8	72LPX105CQ	7/32 7/32	
CCC 50\/	32 (80)	·	32H8PS3805C*	105			73LPX105CQ		-
CCS-58V	16 (40)	Non-Replaceable	16A4CD3756C	56	.043	3/8 lp	90PX56CQ	4.5 mm	-

Lp = Low Profile \* Solid bars, all other bars are laminated.

The part numbers listed above (e.g. 91PXL52CQ) include a two-or three-letter code that references the chain type. See detailed descriptions below.

#### **CHAIN TYPE: LOW-KICKBACK CHAIN**

PX Low-vibration chisel cutters with ramped depth gauges, bumper drive links and standard sequence.

**BPX** Low-vibration chisel cutters with bumper drive links and standard sequence.

**PXL** Low-vibration semi-chisel cutter with ramped depth gauges, bumper drive links and longer top plate.

#### **CHAIN TYPE: PROFESSIONAL CHAIN**

**LPX** Round-ground chisel cutters with bumper drive links and standard sequence.

VXL Low-vibration semi-chisel cutter with ramped depth gauges and longer top plate.

# MEGHO.

# **CHAINSAW ACCESSORIES**

## **Chain Sharpening Files**

Reference the chart on page **29** to find the correct size for your chain.



Part #	File Size (in.)	File Size (mm)	Description
99988801700	5/32	4.0	File, 2-Pack
99988801720	5/32 4.0		File, (5 boxes of 12)
99988801701	11/64	4.5	File, 2-Pack
99988801721	11/64	4.5	File, (5 boxes of 12)
99988801702	3/16	4.8	File, 2-Pack
99988801722	3/16	4.8	File, (5 boxes of 12)
99988801703	13/64	5.2	File, 2-Pack
99988801723	13/64	5.2	File, (5 boxes of 12)
99988801704	7/32	5.5	File, 2-Pack
99988801724	7/32	5.5	File, (5 boxes of 12)
99988801760	6	152	Flat File, Box of 12
99988801761		Plastic Fil Blue, F	/
99988801762	(		e Handle, tail Pkg of 1
99988801763	0		e Handle, lay Box of 20

# **Chain Sharpening Kits**

Kit includes (2) round files, (1) flat file, file guide, depth gauge, and plastic handle.



Kit Part #	Size (in.)
99988800720	5/32
99988800721	11/64
99988800722	3/16
99988800723	13/64
99988800724	7/32

#### **Bar & Chain Combos**

Part #	Length (in.)	Model(s)
12A0CD91PX	12	CS-271T/303T/310
14A0CD91PX	14	CS-303T/310/3510
16A0CD91PX	16	CS-303T/310/3510/400
18A0CD91PX	18	CS-400
20D0AS72LPX	20	CS-590



**Bumper Spike** 

Part#: 99988802100 - CS-590

(optional right side mount)
Part#: C305000070 - CS-271T
Part#: C304000000 - CS-2511P/T
(optional left side mount)

# **Chainsaw Tip Guard**

Part#: 2894902 - CS-2511P/T through CS-400 Part#: 2893202 - CS-4510 through CS-680P



#### Fastension™

Allows for quick and easy chain adjustments without tools. For CS-400 only.

Part#: 99988802200

# Palm Debris Guard

Part#: 91208 - CS-361P Part#: 91209 - optional CS-355T

Part#: A127000480 optional CS-2511P/T



## **Plastic Scabbard**

Part#: 99988801595 - Retail Pkg. of 1 Part#: 89850308034 - Display Box of 12



# **Felling Wedges**

Part #	Length (in.)	Description	Qty.
99988801802	5.5	Smooth	24
99988801803	5.5	Spiked	24
99988801806	5.5	Smooth	1
99988891807	5.5	Spiked	1
99988801800	8	Smooth	12
99988801801	8	Spiked	12
99988801804	8	Smooth	1
99988801805	8	Spiked	1

# Stump Vise

Part#: 99988801808



## ToughChest™ Chainsaw Cases

Does not fit CS-620PW, CS-7310P or CCS-58V. Dimensions: 20 in. (L)  $\times$  12 in. (W)  $\times$  12.5 in. (H) without scabbard.

ToughChest™ - 20 in. Chainsaw Case ECHO saws up to 20 in. bar.

Part#: 99988801210 - 37.75 in. length with scabbard

## ToughChest™ - 24 in. Chainsaw Case

ECHO saws up to 24 in. bar.

Does not fit CS-590 with 24 in. DOAS bar Part#: 99988801211 - 41 in. length with scabbard

# 32 in. Scabbard only for ToughChest™ - 20 in. & 24 in.

ECHO saws up to 32 in. bar.

Part#: 99988801212



## 20 in. Chainsaw Carry Bag

Dimensions: 18.5 in. (L) x 12 in. (W) s 11.5 (H).

Part#: 103942147



#### **Small Chainsaw Case**

Fits most small to medium-sized saws and ECHO saws up to CS-501P with an 18 in. bar. Length with scabbard: 33 in.

Part#: 99988801213



#### **Arborist Pants\***

Expandable 30 in. - 42 in. waist. Meets OSHA standards for leg protection. UL classified in accordance with ASTM F1897-2014. Length 32 in.

Part#: 99988801304 (32 in. - 34 in. waist)
Part#: 99988801305 (36 in. - 38 in. waist)
Part#: 99988801306 (40 in. - 42 in. waist)
Part#: 99988801307 (44 in. - 46 in. waist)



## Chainsaw Safety Kit\*

Includes Chainsaw safety helmet system, safety glasses, work gloves (L), and professional apron style leg chaps. Length 36 in.

Part#: 99988801527



#### **Chainsaw Gloves**

Features two layers of Kevlar® on the back for cut resistance, and foam pads on the palm for vibration reduction.

100% goatskin leather.

Part#: 99988801600 (M)
Part#: 99988801601 (L)
Part#: 99988801602 (XL)
Part#: 99988801603 (XXL)



# Chainsaw Chaps\*

Expandable 30 in. - 42 in. waist. Meets OSHA standards for leg protection. UL classified in accordance with ASTM F1897-2014.

Part#: 99988801300 - 36 in. long, Apron design Part#: 99988801301 - 40 in. long, Apron design Part#: 99988801302 - 36 in. long, Full wrap design Part#: 99988801303 - 40 in. long, Full wrap design



# Chainsaw Safety Helmet System

Hearing NRR 22 dB(A) rated.

Part#: 99988801500

Replacement Parts:

Part#: 99988801501 - Harness Part#: 99988801502 - Screen

Part#: 99988801503 - Visor Frame Part#: 99988801504 - Ear Muffs

\*ECHO recommends the use of personal protective equipment when operating ECHO power equipment. Chainsaw chaps and pants may not provide the same level of protection with cordless Chainsaws as with gas Chainsaws.



ECHO Power Pruners provide extra long reach for fast, easy and safe tree pruning while keeping your feet on the ground. Available in either fixed length or telescoping configurations, a Power Pruner can provide a reach of over 12 feet depending on the model (and even longer with optional extensions). The lightweight design and comfortable controls ensure maximum operator comfort. Heavy-duty gearboxes feature dual-sealed bearings and spiral cut steel gears for maximum lubrication, durability and cutting performance. An adjustable oiler delivers the right amount of oil, every time, for exceptional chain lubrication. The chain tensioning system improves cutting performance and extends bar and chain life. ECHO Power Pruners deliver commercial-grade performance and optimum tree care versatility.



# **PPF-225**

#### POWER PRUNER

A light weight around-the-house pruner for small to medium sized branches.

- i-30™ starter reduces starting effort by 30%
- · Magnesium gear case with side access chain tensioner
- · Rubber left and right handle grips
- 3' extension also available

Engine CC	21.2
Weight (lbs)	12.8
Overall Length (in.)	94
Bar Length (in.)	10
Fuel Capacity (fl. oz.)	14.2
Oil Capacity (fl. oz.)	6.6







(Fixed only)

Fits all PPF models. Extended reach up to 10 ft. 9 in.

Part#: 99946400011

#### 4-ft. Extension

(Telescoping only)

Fits all PPT models. Extended reach up to 16 ft. 2 in.

Part#: 99946400023







### **POWER PRUNER**

A professional fixed length model with power for large branches.



- · Overmolded front and rear hand grip for extreme comfort
- · Magnesium gear case with side access chain tensioner
- · Heavy-duty steel outer shaft for rigidity and control
- Automatic, adjustable oiler to match cutting conditions

Engine CC	25.4
Weight (lbs)	13.2
Overall Length (in.)	96
Bar Length (in.)	12
Fuel Capacity (fl. oz.)	20.6
Oil Capacity (fl. oz.)	6.6



A professional telescoping model for higher branches and loop handle for more leverage.





- · Overmolded rear hand grip for extreme comfort
- · Magnesium gear case with side access chain tensioner
- · Ribbed fiberglass outer shaft for rigidity and control
- Automatic, adjustable oiler to match cutting conditions

Engine CC	25.4
Weight (lbs)	17.4
Overall Length (in.)1	07-146
Bar Length (in.)	12
Fuel Capacity (fl. oz.)	20.6

Oil Capacity (fl. oz.) ..... 6.6









A professional telescoping model for higher branches with an in-line handle for extra comfort.



- Overmolded rear hand grip for extreme comfort
- Magnesium gear case with side access chain tensioner
- · Ribbed fiberglass outer shaft for rigidity and control
- · Automatic, adjustable oiler to match cutting conditions

Engine CC	25.4
Weight (lbs)	17
Overall Length (in.)	107-146
Bar Length (in.)	12
Fuel Capacity (fl. oz.)	20.6
Oil Capacity (fl. oz.)	6.6

	BAR			CHAIN					
Power Pruner® Models	Length in. (cm)	Nose	Bar Part #	Drive Link Count	Gauge (in.)	Pitch (in.)	Chain Part#	File Size (in.)	
PPF-225, 99944200532	10 (25)	Sprocket Nose	10A0CD3739C	39	.050	3/8 lp	91VXL39CQ	5/32	
PPF-2620, PPT-2620/H	12 (30)	Sprocket Nose	12A0CD3744C	44	.050	3/8 lp	91VXL44CQ	5/32	
PPF-225, 99944200532	10 (25)	Sprocket Nose	10A4CD3739C	39	.043	3/8 lp	90PX39CQ	4.5 mm	
PPF-2620, PPT-2620/H	12 (30)	Sprocket Nose	12A4CD3744C	44	.043	3/8 lp	90PX44CQ	4.5 mm	

lp=Low Profile \* solid bars, all other bars are laminated

The part numbers listed above (e.g. 91PXL52CQ) include a two-or three-letter code that references the chain type. See detailed descriptions below.

#### **CHAIN TYPE: LOW-KICKBACK CHAIN**

Low-vibration chisel cutters with ramped depth gauges, bumper drive links and standard sequence.

Low-vibration chisel cutters with bumper drive links and standard sequence.

Low-vibration semi-chisel cutter with ramped depth gauges, bumper drive links and longer top plate.

#### **CHAIN TYPE: PROFESSIONAL CHAIN**

LPX Round-ground chisel cutters with bumper drive links and standard sequence.

VXL Low-vibration semi-chisel cutter with ramped depth gauges and longer top plate.

	225	2620	2620	PPT-2620H
POWER PRUNERS®	PPF-225	PPF-2620	PPT-2620	PPT-
Features and Benefits				
Tool-less air filter cover for easy access	•	•	•	•
2-stage air filter for improved filtration and long engine life		•	•	•
i-30 <sup>™</sup> starting system for 30% starting effort reduction	•			
Digital ignition system for easy starting	•	•	•	•
Purge bulb for easy starting	•	•	•	•
Galvanized steel tube for rigidity and durability	•	•		
Aluminum inner drive shaft for torsion strength and light weight			•	•
Ribbed fiberglass outer shaft for rigidity and control			•	•
Ergonomic loop handle with rubber grip for comfort and handling			•	
In-line handle with rubber grip for comfort	•	•		•
Shock-absorbing drive shaft prevents damage to shaft	•	•	•	•
Automatic, adjustable oiler to match cutting conditions	•	•	•	•
Side-access chain tensioner for quick chain adjustments	•	•	•	•
Multi-layer flexible cable drive with lifetime warranty for buyer confidence	•	•	•	•
Rubberized front hand grip for comfort and vibration reduction	•	•		
1.5:1 gear ratio provides torque needed to cut large branches	•	•	•	•
Telescoping shaft for a variety of cutting heights			•	•

# **SPECIFICATIONS**

Model	Engine Disp. (cc)	Starting System	Fuel Cap. (fl. oz.)	Oil Cap. (fl. oz.)	Length Collapsed (in)	Length Extended (in)	Optional Extension (ft)	Bar Length (in)	Dry Weight* (lb)
PPF-225	21.2	i-30™	14.2	6.6	94	-	3	10	12.8
PPF-2620	25.4	Standard	20.6	6.6	96	-	3	12	13.2
PPT-2620	25.4	Standard	20.6	6.6	107	146	4	12	17.4
PPT-2620H	25.4	Standard	20.6	6.6	107	146	4	12	17.0

\*without bar and chain



Our powerful, yet easy-to-use CSG-7410 cut-off saw gives you exceptional cutting performance. With a class-leading high-torque drive system, you have a greater ability to cut through blocks or concrete without stalling. The CSG-7410 is easy to start thanks to a spring-assist starter, decompression valve, choke with fast idle and purge bulb. The reversible cutting arm enables you to switch from a standard position to outside mount for flush cutting.





Includes abrasive wheel. Diamond wheel (shown) sold separately.

# **CSG-7410**

### **CUT-OFF SAW**

Perfect for pavers, bricks, concrete, retaining walls and other various hardscaping and construction jobs.

- Four-stage air filtration system protects engine from harmful dust ingestion
- · Decompression valve and purge bulb for easier starting
- Side-access belt tensioner for easier belt adjustment
- Reversible cutting arm can be moved to enable cutting near a wall or close to the ground

Engine CC	73.5
Weight (lbs)	23.6
Wheel Diameter (in.)	14
Fuel Capacity (fl. oz.)	23.7



# CUT-OFF SAW ACCESSORIES



# NEW

#### **Pressurized Water Tank**

Fits the CSG-7410 and most competitive cut-off saws.

Part#: 99988805000

# **SPECIFICATIONS**

Engine Disp.	Max. Engine Speed	Spindle Speed	Dry Weight	Wheel Diameter	Max. Cutting Depth	Arbor Size
73.5 cc	9,800 rpm	3,820 rpm	23.6 lbs.	14 in.	4.9 in.	20 & 25.4 mm



ECHO Perfect Edge™ edgers create that perfect manicured look for commercial properties and residential home sites. An ECHO edger delivers superior power and durability in light weight and easy-to-maneuver units. The PE-2620 and PE-2620S feature a Pro-Torque™ gear case that provides 20% more torque than traditional equipment and a clog-resistant shield to keep material from piling up and slowing down the blade.





The perfect model to give residential sidewalks that professional look.

- · Durable, molded shield and rubber debris flap reduce material kickback
- · Heavy-duty, height-adjustable guide wheel with solid rubber tread and captive hardware
- · Tool-less access air filtration system for convenient in-field servicing
- · Large front handle for an easy, controlled grip

Engine CC	. 21.2
Weight (lbs)	. 13.1
Blade Length (in.)	. 7.75
Fuel Capacity (fl. oz.)	. 14.2



CURVED SHAFT FOGER

A powerful, professional curved shaft model for commercial and industrial use.









- · Tool-less access, two-stage air filtration system dramatically increases ease of maintenance
- · 2:1 gear reduction to power through tough overgrown grass
- Easy height-adjustment wheel with captive hardware

Engine CC	25.4
Weight (lbs)	14.1
Blade Length (in.)	7.75
Fuel Capacity (fl. oz.)	20.6

# **ECHO** EDGER ACCESSORIES



Standard .090 in. thickness, 7.75 in in length.

Part#: 69601552632 - Package of 2 Part#: 99944201000 - Bulk pack of 50



7.75 in in length.

Part#: 69601553630 - Package of 2 Part#: 99944205000 - Bulk pack of 25

## **CRACK CHASER WIRE WHEEL**

Clears debris from driveways, cracks, sidewalks or paved bricks. 6.875 in. diameter, 25 mm arbor.

Part#: 99944206000








#### STRAIGHT SHAFT EDGER

A powerful, professional straight shaft model for commercial and industrial use.



- Contoured, aluminum debris shield with a cut-away, open face to reduce clogging
- Tool-less access, two-stage air filtration system dramatically increases ease of maintenance
- 2:1 gear reduction to power through tough, overgrown grass

Engine CC	25.4
Weight (lbs)	14.1
Blade Length (in.)	7.75
Fuel Capacity (fl. oz.)	20.6

EDGERS EDGERS	PE-255	PE-2620	PE-2620S
Features and Benefits			
Tool-less air filter cover for easy access	•	•	•
Professional-grade felt air filtration for long engine life	•		
2-stage pleated air filtration for long engine life		•	•
i-30™ starting system for 30% starting effort reduction	•		
Digital ignition system for easy starting	•	•	•
Purge bulb for easy starting	•	•	•
Heavy-duty cylinder/piston plating for increased engine life		•	•
Ergonomic throttle handle with rubber grip for comfort		•	•
Ergonomic, adjustable front handle for a custom fit	•	•	•
Pro-Torque™ gear case for long-lasting durability		•	•
Metal skid plate for reduced wear to debris shield	•		
Extra wide skid plate for added gear case protection		•	•
Durable, molded shield for reduced material kickback	•		
Clog-resistant, open-face metal shield for reduced clogging		•	•
Sight line on shield for straighter cuts	•	•	•
Heavy-duty adjustable guide wheel with solid rubber tread	•	•	•
Powerhead components made from high-grade magnesium for light weight and durability		•	•
Dual piston ring design for long engine life		•	•
Extra heavy-duty engine vibration reduction system		•	•

### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Fuel Cap. (fl. oz.)	Starting System	Debris Shield	Blade Length (in)	Blade Thickness (in)	Dry Weight (lb)
PE-225	21.2	14.2	i-30™	High-Impact Nylon	7.75	0.090	13.1
PE-2620	25.4	20.6	Standard	Die-Cast Metal	7.75	0.090	14.1
PE-2620S	25.4	20.6	Standard	Die-Cast Metal	7.75	0.090	14.2



Flower bed and mulch bed edges erode over time and need to be redefined to maintain a fresh, welcome appearance. The BRD-2620 cuts a crisp, beveled groove along the turf edge, leaving a professional, manicured finish. The replaceable six-finger cutting claw is manufactured from high-grade steel with specially designed carbide tips on each cutter for improved durability and performance that does the job 7x faster than a shovel!









The professional choice for redefining bed edges that erode over time.

- · Replaceable, patented, 6-finger steel blade with brazed carbide tips for durability and performance
- · Tool-less access, two-stage air filtration system dramatically increases ease of maintenance
- · Cast aluminum debris shield combined with high-impact nylon shield for reduced material kickback
- 59" straight shaft with flex cable drive for outstanding reach

Engine CC	25.4
Weight (lbs)	17.7
Blade Length (in.).	7.75
Fuel Capacity (fl. oz.)	20.6





### **BED REDEFINER ACCESSORIES**

#### REPLACEMENT CLAW

Exclusively for use with the BRD-2620 and the PAS Bed Redefiner attachment.

Part#: 99944208000



#### **SPECIFICATIONS**

Engine Disp. (cc)	Fuel Cap. (fl. oz.)	Gear Ratio	Debris Shield	Dry Weight (lb.)
25.4	20.6	2:1	Die-Cast Metal/Nylon	17.7



For professionals who demand performance, ECHO hedge trimmers deliver and are available in single-sided and double-sided blade configurations, as well shafted models. ECHO hedge trimmers are tough, reliable and loaded with intelligent features like: a throttle lock-out to help prevent accidental blade engagement, commercial-grade gear cases and cutting blades for the heaviest applications, and vibration-reducing engine mounts and padded handles for operator comfort. Every hedge trimmer uses ECHO-exclusive RazorEdge® blades, which are laser cut and precision ground for long-lasting sharpness. Three sharpened edges per cutting tooth start cutting before the tooth engages, giving you the most efficient cut possible.



### **SUGGESTED HEDGE TRIMMER APPLICATION**

LOW/SMALL TRIMMING	MEDIUM TRIMMING	TALL/LARGE TRIMMING
HC-2810	HCA-2620S	HCA-2620
HC-2210	SHC-225	SHC-2620S
HC-155	SHC-225S	SHC-2620
HC-2020	HCS-3810	SHC-225
	HCS-2810	



Professional features and a long blade length make it a solid choice for any hedge trimming.

- 24" double-sided, double-reciprocating RazorEdge® blades are precision ground and laser cut for long-lasting sharpness
- Ergonomic front and rear handles for a comfortable grip
- Redesigned gear box provides dependability and durability
- Commercial-duty air filtration system for long engine life

Engine CC	21.2
Weight (lbs)	11.3
Blade Length (in.)	24
Fuel Capacity (fl. oz.)	16.9

## HC-2020

**HEDGE TRIMMER** 



A lightweight option with a shorter blade length perfect for smaller bushes and hedge trimming around the house.

- 20" double-sided, double-reciprocating RazorEdge® blades are precision ground and laser cut for long-lasting sharpness
- Class-leading 10 lbs. dry weight for reduced fatigue
- Large ergonomic front and rear handles for increased comfort and control
- Commercial-duty air filtration system for long engine life

Engine CC	21.2
Weight (lbs)	10
Blade Length (in.)	20
Fuel Capacity (fl. oz.)	13.2



HG-2210/HG-2810 Light weight, professional double-sided performance available in two blade length performance available in two blade lengths.





- Double-sided, double-reciprocating RazorEdge® blades are precision ground and laser cut for long-lasting sharpness
- 3-position 180 degree rotating handle for increased maneuverability
- Front-facing exhaust prevents plant damage
- Full-spring suspension system reduces vibration for operator comfort

Engine CC	21.2
Weight (lbs)	
Blade Length (in.)	22/28
Fuel Capacity (fl. oz	) <b>12.5</b>



### HCS-2810/HCS-381

Features light weight, professional single-sided performance available in two blade lengths.





- Single-sided, double-reciprocating RazorEdge® blades are precision ground and laser cut for long-lasting sharpness
- Full-length debris shield for reduced cleanup time
- Front-facing exhaust prevents plant damage
- Full-spring suspension system reduces vibration for operator comfort

Engine CC	21.2
Weight (lbs) 10.2/	10.8
Blade Length (in.) 2	8/38
Fuel Capacity (fl. oz.)	12.5

## SHAFTED HEDGE



With two different shaft lengths, this is an excellent around-the-house choice for taller bushes and hedges.

- 20" double-sided, double-reciprocating RazorEdge® blades are precision ground and laser cut for long-lasting sharpness
- i-30™ starter reduces starting effort by 30%
- Vibration reduction system for increased comfort
- Commercial-duty air filtration system for long engine life

Engine CC	21.2
Weight (lbs)	
Shaft Length (in.)	20/33
Blade Length (in.)	21
Fuel Capacity (fl. oz	) <b>14.2</b>

### **SHC-2620/ SHC-2620S**


#### **HEDGE TRIMMERS**



Most powerful shafted hedge trimmers available for professional use in two different shaft lengths.







SHC-2620S

- Tool-less access, two-stage air filtration system dramatically increases ease of maintenance
- 7 degree angled shaft provides a wide-angle view for trimming complex shapes (for SHC-2620 only)
- Overmolded front and rear hand grips for extreme comfort

Engine CC 25.4
Weight (lbs) 13/12.7
Shaft Length (in.) 51/42
Blade Length (in.) 21
Fuel Capacity (fl. oz.) 20.6


### NEW HCA-2620/ HCA-2620S

### ARTICULATING SHAFTED HEDGE TRIMMERS



Features powerful, professional durability with an articulating gear case in two different shaft lengths.





- Tool-less access, two-stage air filtration system dramatically increases ease of maintenance
- Articulating gear case provides 10 blade settings with a total range of 135 degrees
- Vibration-reduction system isolates front and rear handles from the engine and gear case for operator comfort

Engine CC	25.4
Weight (lbs) 14.3	3/13.6
Shaft Length (in.)	59/33
Blade Length (in.)	21
Fuel Capacity (fl. oz.)	. 20.6

### 

### **HEDGE TRIMMER ACCESSORIES**

#### **Blade Protectors**

Part#: 99988802000 - HC-155 and all SHC models

Part#: 99988802010 - HCA-2620

Part#: 99988802020 - For all single-sided models

Part#: 99988802030 - HC-2020



### RED ARMOR® BLADE CLEANER AND LUBRICANT

Get rid of what's collected along your blade. Our exclusive formula reduces friction, prevents corrosion, and promotes post-trimming plant health.

Part#: 4550012 - 12 fl. oz. bottle



HEDGE TRIMMERS	HC-2020	HC-155	HC-2210	HC-2810	HCS-2810	HCS-3810	SHC-225	SHC-225S	SHC-2620	SHC-2620S	HCA-2620	HCA-2620S
Features and Benefits												
Tool-less air filter cover for easy access	•	•	•	•	•	•	•	•	•	•	•	•
Commercial-grade felt air filter for improved filtration	•	•	•	•	•	•	•	•				
2-stage pleated air filter for improved filtration and long engine life									•	•	•	•
Purge bulb for easy starting	•	•	•	•	•	•	•	•	•	•	•	•
i-30™ starting system for 30% starting effort reduction	•	•	•	•	•	•	•	•				
RazorEdge* laser-cut, double-reciprocating blades for long-lasting sharpness	•	•	•	•	•	•	•	•	•	•	•	•
Blade design with 3 cutting edges for efficient clean cuts	•	•	•	•	•	•	•	•	•	•	•	•
Grease-able gear case for easy maintenance and longer life	•	•	•	•	•	•	•	•	•	•	•	•
Rigid support bars for straighter and more precise cuts	•	•	•	•	•	•	•	•	•	•	•	•
Tip guard prevents blade contact with buildings, fences, or the ground	•	•					•	•	•	•	•	•
3-position 180° rotating handle for a variety of cutting positions			•	•								
Vibration-reduction system isolates front and rear handles from engine			•	•	•	•	•	•	•	•	•	•
Rubber overmolded front handle for increased comfort					•	•	•	•				
Throttle handle with rubber grip for increased comfort					•	•	•	•	•	•	•	•
Cushioned front handle for increased comfort									•	•	•	•
Front facing exhaust prevents plant damage			•	•	•	•						

### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Carb. (w/Purge Pump)	Starting System	Fuel Cap. (fl. oz.)	Blade Length (in)	Shaft Length (in)	Double-Reciprocating Cutter Type	Dry Weight (lb)
HC-2020	21.2	Rotary	i-30™	13.2	20	-	Double Sided	10.0
HC-155	21.2	Rotary	i-30™	16.9	24	-	Double Sided	11.3
HC-2210	21.2	Rotary	i-30™	12.5	22	-	Double Sided	11.0
HC-2810	21.2	Rotary	i-30™	12.5	28	-	Double Sided	11.4
HCS-2810	21.2	Rotary	i-30™	12.5	28	-	Single Sided	10.2
HCS-3810	21.2	Rotary	i-30™	12.5	38	-	Single Sided	10.8
SHC-225	21.2	Rotary	i-30™	14.2	21	33	Double Sided	12.7
SHC-225S	21.2	Rotary	i-30™	14.2	21	20	Double Sided	12.3
SHC-2620	25.4	Rotary	Standard	20.6	21	51	Double Sided	13
SHC-2620S	25.4	Rotary	Standard	20.6	21	42	Double-Sided	12.7
HCA-2620	25.4	Rotary	Standard	20.6	21	59	Double Sided	14.3
HCA-2620S	25.4	Rotary	Standard	20.6	21	33	Double Sided	13.5



The ECHO Pro Attachment Series™ (PAS) is the perfect all-in-one solution. In a word, the system delivers versatility. The application flexibility of this expandable line-up is as limitless as your changing job requirements. When your job requires a change, a simple tool-less coupler makes changing to another tool quick and easy. The PAS system is also economical without having to purchase stand-alone, dedicated units or maintain multiple engines - all you need is one power head and a collection of attachments.





### **PAS-225**

#### **POWER HEAD**

The best choice for many residential yard chores.

- · Tool-less coupler allows for fast, easy changes on multiple attachments
- · Adjustable left-handed grip for desired operator's hand position
- · Vibration reduction system for increased comfort
- · Accepts up to 12 PAS attachments (see page 46 for list)

Engine CC 21.2	
Weight (lbs) 9.4	
Fuel Capacity (fl. oz.) 14.2	
Shaft Length (in.)40.7	







PAS-225 power head with Speed-Feed® 400 trimmer attachment included.

- Tool-less coupler allows for fast easy changes on multiple attachments
- Speed-Feed® 400 trimmer head reloads in seconds without disassembly
- · Durable debris shield with cut-off knife
- Accepts up to 12 PAS attachments (see page 46 for list)

Engine CC2	1.2
Head Weight (lbs)	9.4
Total Shaft Length (in.)	59
Fuel Capacity (fl. oz.)14	4.2
Cutting Head: Speed-Feed® 4	00
Cutting Swath (in.)	17



Value pack that includes PAS-225 power head and Speed-Feed® 400 trimmer and Blower attachments.

- Tool-less coupler allows for fast easy changes on multiple attachments
- Speed-Feed® 400 trimmer head reloads in seconds without disassembly
- Blower attachment features 100 MPH air flow and 317 CFM
- · Accepts up to 12 PAS attachments (see page 46 for list)

Engine CC21	1.2
Head Weight (lbs)	).4
Total Shaft Length (in.)40	).7
Fuel Capacity (fl. oz.)14	1.2
Cutting Head:Speed-Feed® 4	00
Cutting Swath (in.)	17
Max Air Speed at nozzle (mph) 1	00
Air volume at nozzle3	17

### PAS-225VP



Value pack that includes PAS-225 power head and Speed-Feed® 400 trimmer and Curved Shaft Edger attachments.

- · Tool-less coupler allows for fast easy changes on multiple attachments
- Speed-Feed® 400 trimmer head reloads in seconds without disassembly
- · Edger attachment features clog-resistant, open-faced metal shield
- Accepts up to 12 PAS attachments (see page 46 for list)

Engine CC21.	
Head Weight (lbs)9.	4
Total Shaft Length (in.) 59	9
Fuel Capacity (fl. oz.)14.	2
Cutting Head: Speed-Feed® 40	0
Cutting Swath (in.)1	7
Blade Length (in.)7.7	5





### **PAS-2620**

#### **POWER HEAD**

More power for commercial applications

- Tool-less coupler allows for fast easy changes on up to 15 attachments (see page 46 for list)
- · Tool-less access, two-stage air filtration system dramatically increases ease of maintenance
- Engine vibration reducing mounting absorbs engine vibration
- Cushioned front and rear handles increase operator comfort

Engine CC	25.4
Weight (lbs)	9.9
Fuel Capacity (fl. oz.)	20.6
Shaft Length (in.)	40.7





### WEGHO!

#### **PAS ATTACHMENTS**

#### **Curved Shaft Trimmer**

- · Rapid Loader® head
- · Curved shaft for precise trimming
- · Length: 33 in. Weight: 3.9 lbs.

Part#: 99944200615



#### Speed-Feed® 400 Trimmer

- 1.62:1 gear ratio
- Easy-loading Speed-Feed 400®
- · Length: 34 in. Weight: 3 lbs.

Part#: 99944200540



#### **Pro-Torque<sup>™</sup> Trimmer**

- Pro-Torque gear case increases cutting torque by 50%
- ECHOmatic<sup>™</sup> trimmer head
- · Length: 34 in. Weight: 3.2 lbs.

Part#: 99944200615

#### **Bed Redefiner**

- · Patented, replaceable 6-finger steel claw
- · Adjustable support wheel
- · Length: 34.8 in. Weight: 8.5 lbs.

Part#: 99944200465

#### **Curved Shaft Edger**

Pro-Torque<sup>™</sup> gear case

• Blade length: 7.75 in.

· Length: 33 in. Weight: 5.6 lbs.

Part#: 99944200470

#### Tiller/Cultivator

- · 6.5 in tilling swath
- · Heavy-duty gear box
- 42:1 gear reduction
- · Length: 35 in. Weight: 4.6 lbs.

Part#: 99944200513

#### Mid-Reach Hedge Trimmer

- 21 in. double-sided double-reciprocating RazorEdge\* blades
- 37.9 in. length
- · Length: 37.9 in. Weight: 3.63 lbs.

Part#: 99944200640

#### 3' Extension

- Tool-less coupler attaches between the PAS power head and attachment
- Compatible with Power Pruner<sup>®</sup> and all hedge trimmer attachments
- · Length: 36 in. Weight: 2.6 lbs.

Part#: 99944200536

#### Pro Paddle<sup>™</sup>

- 10, 1.625 in. durable rubber fins
- 22.5 in sweeping swath
- Useful for rocks, mulch, pine needles, pine cones, acorns and sand
- Length: 36.5 in. Weight: 11.2 lbs.

Part#: 99944200620



- 1.62:1 gear ratio
- · Includes 8 in. 80-tooth brush blade
- · Length: 33 in. Weight: 2.62 lbs.

Part#: 99944200601

#### **Blower**

- · Solid drive shaft with 4-bearing support
- · Direct-drive fan for efficient power transfer
- · Length: 25 in. Weight: 3.9 lbs.

Part#: 99944200490



#### Straight Shaft Edger

- Pro-Torque<sup>™</sup> gear case
- Blade length: 7.75 in.
- · Length: 33 in. Weight: 5.6 lbs.

Part#: 99944200475

# ...

#### **Standard Hedge Trimmer**

- 21 in. double-sided double-reciprocating RazorEdge® blades
- Length: 50.1 in. Weight: 4.13 lbs.

Part#: 99944200486

#### **Articulating Hedge Trimmer**

- 10 blade positions with range of 135°
- 21 in. double-sided double-reciprocating RazorEdge® blades
- 54.4 in. length (extended), 46.3 in. length (storage position)
- · Length: 64.4 in. Weight: 5.6 lbs.

Part#: 99944200596

#### Power Pruner®

- Heavy-duty gear case and automatic oiler
- Over 8 ft. of total reach
- · Comes with a 10 in. bar and chain
- · Length: 57 in. Weight: 4.8 lbs.


Part#: 99944200532



- 22.5 in. sweeping swath
- Perfect for all surfaces including lawn, concrete and soil
- · Length: 36 in. Weight: 11.2 lbs.

Part#: 99944200553





PRO ATTACHMENT SERIES™	PAS-225	PAS-225VP	PAS-225VPB	PAS-225SB	PAS-2620	CST-58V
Features and Benefits						
Tool-less air filter cover for easy access	•	•	•	•	•	_
Commercial-grade felt air filtration for long engine life	•	•	•	•		_
2-stage air filter for improved filtration and long engine life					•	_
i-30™ starting system for 30% starting effort reduction	•	•	•	•		_
Digital ignition system for easy starting	•	•	•	•	•	-
Purge bulb for easy starting	•	•	•	•	•	_
Heavy-duty cylinder/piston plating for increased engine life					•	-
Ergonomic throttle handle with rubber grip for comfort	•	•	•	•	•	_
Ergonomic, adjustable front handle for a custom fit	•	•	•	•	•	-
Engine vibration-reduction system for operator comfort	•	•	•	•	•	_
Attachment Capability						
Curved Shaft Trimmer	•	•	•	•		
Speed-Feed® Trimmer	•	•	•	•	•	•
Pro-Torque™ Trimmer	•	•	•	•	•	•
Brushcutter	•	•	•	•	•	•
Bed Redefiner					•	
Blower	•	•	•	•	•	
Curved Shaft Edger	•	•	•	•	•	
Straight Shaft Edger					•	•
Tiller/Cultivator	•	•	•	•	•	•
Hedge Trimmer	•	•	•	•	•	•
Mid-Reach Hedge Trimmer	•	•	•	•	•	•
180° Articulating Hedge Trimmer	•	•	•	•	•	•
3 ft. Extension	•	•	•	•	•	
Power Pruner®	•	•	•	•	•	
Pro Paddle™					•	
Pro Sweep™					•	

### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Carb. (w/Purge Pump)	Fuel Capacity (fl. oz.)	Starting System	Length* (in.)	Dry Weight (lb)*
PAS-225	21.2	Rotary	14.2	i-30™	40.7	9.4
PAS-225VP	21.2	Rotary	14.2	i-30™	40.7	9.4
PAS-225VPB	21.2	Rotary	14.2	i-30™	40.7	9.4
PAS-225SB	21.2	Rotary	14.2	i-30™	40.7	9.4
PAS-2620	25.4	Rotary	20.6	Standard	40.7	9.9

\*Power head only



ECHO Sprayers are lightweight and easy to use. They are available in handheld and backpack styles. The entire backpack product line features light weight tanks with UV inhibitors, ergonomic pump handles, 28" wands with a variety of nozzles and pumps with Viton® seals, 4-stage filters and fold-away handles for easy storage.





A lightweight, handheld model great for in-house misting or flower shop use.

- · Includes adjustable brass and plastic nozzles
- Viton® pump seal for maximum durability
- · Ergonomic handle for easy pumping and carrying
- · Fully assembled

ank capacity (gal)375	
/eight (lbs) <b>9</b>	
ressure Rating (psi)45	
ank Opening (in.)1.75	



A lightweight, handheld model designed for larger applications when a backpack model is not feasible.

- · 2-gallon tank with UV inhibitors
- 28 in. stainless steel wand features three nozzles: brass adjustable, fixed fan and fixed cone
- Pump with ergonomic handle and Viton® seals pressurizes with 45% fewer pumps
- · Tank marked in both gallons and liters for convenience

Tank capacity (gal)	2
Weight (lbs)6.	5
Pressure Rating (psi)4	5
Tank Opening (in.)	4

MS-31H Handheld Sprayer



A lightweight, handheld model designed for extended spraying.

- · 3-gallon tank with UV inhibitors
- 28 in. stainless steel wand features three nozzles: brass adjustable, fixed fan and fixed cone
- Pump with ergonomic handle and Viton® seals pressurizes with 45% fewer pumps
- · Tank marked in both gallons and liters for convenience

Tank capacity (gal)3
Weight (lbs)
Pressure Rating (psi)45
Tank Opening (in.)4

CF Valve - 29 PSI

Part#: 99944100510



CF Valve - 15 PSI

Part#: 99944100508



CF Valve - 21 PSI

Part#: 99944100509



Adding constant flow valves to your wand or boom can help in conserving chemical mixtures while reducing waste and time by delivering a consistent flow control, independent of input pressure.



### MS-41BP

#### BACKPACK SPRAYER

Increased capacity for larger, outdoor applications

- · 4-gallon tank with UV inhibitors
- 30 in. stainless steel wand features three nozzles: brass adjustable, fixed fan and fixed cone
- Critical seals and O-rings made of Viton® formulation for increased durability
- · Ergonomic pump and swing-away handle

Tank capacity (gal)	4
Weight (lbs)	9.9
Pressure Rating (psi)	.90
Tank Opening (in.)	4



### MS-41BPD

#### **BACKPACK SPRAYER**

The best performing sprayer on the market combines two pump technologies.

- Combines higher pressure of a piston pump with extended life span of a diaphragm pump
- 28 in. stainless steel wand with brass nozzle for extended reach
- · Large 6 in. ID cap opening largest in the market
- Double-thick shoulder straps adds additional comfort

Tank capacity (gal)4
Weight (lbs)10.2
Pressure Rating (psi)90
Tank Opening (in.)6



### MS-53BPE

#### **BACKPACK SPRAYER**

A large capacity sprayer for the largest applications featuring an ergonomic "euro"-style tank design.

- · 5-gallon tank with UV inhibitors
- 28 in. wand trigger with three nozzles for application versatility
- Fold-away pump handle with storage clip
- Critical seals and O-rings made of Viton® formulation for increased durability

٦	Tank capacity (gal)	5
	Weight (lbs)	
F	Pressure Rating (psi)	90
٦	Tank Opening (in.)	4.5



### **SPRAYER ACCESSORIES**

#### 40 in. Stainless Steel Wand

Part#: 99944100507

#### 40 in. Polypropylene Wand

Part#: 99944100506



#### 20 in. Stainless Steel Wand

Part#: 99944100505



#### 20 in. Brass Wand

Part#: 99944100504



#### 2-Nozzle Polypropylene Boom

· Length: 18 in.

• Sprays approx. 48 in. swath

Part#: 99944100500

### 3-Nozzle Polypropylene Boom

• Length: 34 in.

· Sprays approx. 70 in. swath

Part#: 99944100501

#### 4-Nozzle Polypropylene Boom

· Length: 40 in.

· Sprays approx. 80 in. swath

Part#: 99944100502

#### **Fan Spray Nozzle**

Part#: 99944100350



#### **Spot Spraying Shield with Nozzle**

• Protects plants and flowers from overspray

• 80% angle for full coverage spraying

Part#: 99944100503



SPRAYERS	MS-1H	MS-21H	MS-31H	MS-41BP	MS-41BPD	MS-53BPE
Features and Benefits						
Tank with UV inhibitors for long life	•	•	•	•	•	•
Tank marked in both gallons and liters for convenience		•	•	•	•	•
Ergonomic pump handle for comfortable operation	•	•	•	•	•	•
Fold-away handle with left or right hand operation				•	•	•
Piston-style pump for efficient operation	•	•	•	•	•	•
3-stage filtration for longer pump and wand life				•	•	
Viton™ formulation seals for increased durability	•	•	•	•	•	•
Pressure-relief valve for convenient operation		•	•			
28 in. wand trigger with three nozzles for application versatility		•	•	•	•	•
Combo piston/diaphragm pump for extended lifespan					•	

### **SPECIFICATIONS**

Model`	Туре	Capacity (gal)	Max. Pressure Rating (psi)	Weight (lb)
MS-1H	Handheld	0.375	45	0.9
MS-21H	Handheld	2	45	6.5
MS-31H	Handheld	3	45	7.6
MS-41BP	Backpack	4	90	9.9
MS-41BPD	Backpack	4	90	10.2
MS-53BPE	Backpack	5	90	12.4

### **CHEMICAL/SOLVENT CHART**

Chemical/Solvent	MS-1H	MS-21H	MS-31H	MS-41BP	MS-53BPE	Chemical/Solvent	MS-1H	MS-21H	MS-31H	MS-41BP	MS-41BPD	MS-53BPE
Acetone						Isopropyl Alcohol	•	•	•	•	•	•
Asphalt						Kerosene	•	•	•	•	•	•
Benzene	•	•	•	•	•	Lacquer Solvents						
Bleach Solutions*	•	•	•	•	•	Latex Paint						
Boric Acid	•	•	•	•	•	Methyl Ethyl Ketone						
Denatured Alcohol	•	•	•	•	•	Naphtha	•	•	•	•	•	•
Diesel Fuel	•	•	•	•	•	Ridomill®	•	•	•	•	•	•
Diozone	•	•	•	•	•	Roundup®	•	•	•	•	•	•
Dow Chemical Path Finder	•	•	•	•	•	Sulfuric Acid	•	•	•	•	•	•
Enamel Paint						Toluene						
Ethyl Alcohol	•	•	•	•	•	Wettable Powders					•	
Hydrochloric Acid	•	•	•	•	•	Xylene	•	•	•	•	•	•

\*up to 5% concentration



The ultimate combination of technology and output to deliver peace of mind and power, when and where you need it. Our line-up of inverters and generators is packed with professional convenience features that help provide easy-to-use power. Whether you're tailgating, RVing, relying on household appliances during power outages, or need to do a job where access to electricity is limited, you can count on our innovation to see you through any task.





### 

BlueTooth® ECHO Command™ integration to monitor load, fuel, and run time.



ECHO COntrol® senses and manages CO output, including an auto-shutdown when levels become unsafe.





A compact and super-quiet inverter ideal for RVing and tailgating.

- Ultra-quiet operation compared to conventional generators
- · Auto-idle fuel-saving technology
- Computer controlled power output to safely charge electronics
- · Parallel capable

60
1200
33
9
2
0.69
<b>% Load</b>



**EGi-2300** 



A cost-effective and quiet solution for camping, tailgating and powering home essentials.

- BlueTooth® ECHO Command™ app integrated to monitor load, fuel level & run time
- ECHO COntrol® function senses and manages
   CO output
- Computer controlled power output to safely charge electronics
- Ultra-quiet operation compared to conventional generators

Engine CC	80
Max. Wattage (W) 2300	W
Weight (lbs.)	59
Max. Amp (A) 15	5A
USB Ports	2
Fuel Capacity (gal.)1.2 g	al.
Run Time 5.5 hours @ 50% Lo	ad





### NEW EGi-3600LN

INVERTER



Features ultra-quiet performance and power designed for use in close guarters.

- · Easy electric start with recoil back up
- Auto-idle fuel-saving technology
- LED control panel displays fuel level and power usage
- · Parallel capable

Engine CC	212
Max. Wattage (W)	3600W
Weight (lbs.)	107
Max. Amp (A)	30A
USB Ports	2
Fuel Capacity (gal.)	2.2 gal.
Run Time <b>8.5 hours @ 50%</b>	6 Load







### **EGi-4000**

INVERTER



Packed with applications for camping, tailgating, home essentials, recreational and idle charging including ECHO 58V batteries.

- BlueTooth® ECHO Command™ app integrated to monitor load, fuel level & run time
- ECHO COntrol® function senses and manages CO output
- Computer controlled power output to safely charge electronics
- · Auto-idle fuel-saving technology

Engine CC212	
Max. Wattage (W) 4000W	
Weight (lbs.)89	
Max. Amp (A) <b>30</b>	
USB Ports2	
Fuel Capacity (gal.)3	
Run Time 10 hours @ 50% Load	







## EG-3500 CONVENTIONAL



An ideal solution for job sites and home power outages or emergencies.

- Automatic voltage regulator to maintain constant voltage & power
- · Covered outlets protect unit while storing
- · Includes fuel gauge and low oil shut down
- · Circuit breaker protection

Engine CC212	
Max. Wattage (W)3500	
Weight (lbs.) 110	
Max. Amp (A)29	
Fuel Capacity (gal.)4	
Run Time 10 hours @ 50% Load	



## EG-10000 CONVENTIONAL



ECHO's highest power generator designed for remote operations, large job sites and home emergencies.

- Automatic voltage regulator to maintain constant voltage & power
- · Easy electric start with recoil back up
- · 3-in-1 digital meter with access to critical information
- · Includes fuel gauge and low oil shut down

Engine CC420	
Max. Wattage (W)10,000	
Weight (lbs.)212	
Max. Amp (A) <b>75</b>	
Fuel Capacity (gal.) 6.6	
Run Time 8 hours @ 50% Load	





### **MECHO: NEW GENERATOR ACCESSORIES**

#### **DC Charge Cables**

Designed to charge 12-volt DC batteries for automotive and recreational vehicles.

Part#: 99988804000 - EGi-1200. EGi-3600LN



#### **Parallel Kit**

Combine the power output of (2) inverter generators.

Part#: 99988804001 - EGi-1200, EGi-3600LN

Part#: 99988804002 - EGi-2300

GENERATORS	EGi-1200	EGi-2300	EGi-3600LN	EGi-4000	EG-3500	EG-10000
Features and Benefits						
Ultra-quiet operation	•	•	•			
Auto-idle saves fuel	•	•	•	•		
Convenient carrying handle	•	•				
Parallel kit capable	•	•	•			
Compact ergonomic frame					•	•
Folding handle and easy rolling flat-free tires			•	•	•	•
Covered outlets and circuit breaker protection		•		•	•	•
Low oil shutdown	•	•	•	•	•	•
Electric start with recoil back-up			•			•
3-in-1 digital meter displays voltage			•			•
Includes fuel gauge & low oil indicator		•	•	•	•	•
Bluetooth Command™ app to monitor functionality		•		•		
Telescoping handle & easy rolling flat-free tires		•				
Carbon monoxide shutdown sensor		•		•		
On-board displays fuel level, runtime & load level		•	•	•		

### **SPECIFICATIONS**

Model	Running Watts	Max Watts	Rated Amps	120V Duplex	120V Twistlock	240V 30 AMP Twist- lock	USB Outlets	RV Plug Outlet	Fuel Tank Capacity	Run Time @ 50% Load	dB(A) Lev- els at 23 Ft (7M)	Unit Weight (lbs.)
EGi-1200	1000W	1200W	8.3	1	-	-	2	-	0.69 gal. 2.6 l	5.2	57 dB(A) @ 25% load	33
EGi-2300	1800W	2300W	15	1	-	-	2	-	1.2 gal. 4.5 l	5.5	57 dB(A) @ 25% load	59
EGi-3600LN	3000W	3600W	25	1	1	-	2	-	2.2 gal.	8.5	63 dB(A) @ 25% load	107
EGi-4000	3400W	4000W	20 Du- plex 30 RV	1	-	-	2	1	3.0 gal. 11.4 l	10	67 dB(A) @ 25% load	89
EG-3500	2800W	3500W	23.3	2	1	-	-	-	3.96 gal. 15 l	10	72 dB(A) @ full load	110
EG-10000	7500W	10000W	59.2	2	1	1	-	-	6.6 gal. 25 l	8	84 dB(A) @ full load	212



Whether you're a professional wanting to quickly clean dirty equipment, or add to your available services, or a homeowner looking to clean your deck or siding, ECHO's line of pressure washers will satisfy a wide range of needs. Make clean up fast, easy and fun to do and see immediate results watching dirt and grime get flushed away. Each model is designed to be durable and cost-effective while providing maximum productivity and convenience.



PWE-1800
PRESSURE WASHER


Powerful, entry-level unit for cleaning windows, driveways, car wheels and more.

- Uses 80% less water than a standard garden hose
- · High quality electric motor for extended use
- · Integrated hose wheel for hose storage
- Variable pressure spray & turbo nozzles to handle a variety of needs

Power Type 13 AMP Electric	
Max. PSI 1,800	
Weight (lbs.) 30	
Max. Gallons per Min 1.3	
PumpAxial Cam	
Hose Length (ft.) 20	







More powerful unit for cleaning sidewalks, driveways, decks and siding.

- · Easy start axial cam pump system
- · 4-stroke engine provides quiet operation
- 2-stage air filtration system promotes longer engine life
- · Reversible handle for easy storage

Engine CC 212	2
Max. PSI 3,100	)
Weight (lbs.) 80	)
Max. Gallons per Min 2.5	5
Pump Axial Cam	1
Hose Length (ft.)25	5
Number of Nozzles4	ļ





**PW-3200** 



Designed for occasional commercial use for stripping finishes, flushing built-up debris on patios and more.

- · Easy start axial cam pump system
- · 4-stroke engine provides quiet operation
- · Pro-style wand with auxiliary handle
- · On-board storage for nozzles, hose and wand
- · Reversible handle for easy storage

Engine CC 212
Max. PSI 3,200
Weight (lbs.) 82
Max. Gallons per Min 2.5
Pump Axial Cam
Hose Length (ft.)30
Number of Nozzles 5





# PW-3600 WASHFR

Increase in pressure for more demanding commercial uses.

- · Triplex pump for maximum strength and durability
- · 4-stroke engine provides guiet operation
- · Pro-style wand with auxiliary handle
- · On-board storage for nozzles, hose and wand
- · Reversible handle for easy storage

Engine CC 21	2
Max. PSI 3,60	0
Weight (lbs.) 8	6
Max. Gallons per Min 2.	5
PumpTriple	X
Hose Length (ft.) 3	5
Number of Nozzles	5





## **PRESSURE** WASHER

Incredible professional power for the toughest jobs.

- · Easy start AR Triplex pump system
- Honda® GX390 engine for ultimate durability
- · Pro-style wand with auxiliary handle
- · Heavy-duty hose withstands the elements
- · Reversible handle for easy storage

Engine CC	389
Max. PSI 4	,200
Weight (lbs.)	145
Max. Gallons per Min	4
PumpAR Tri	plex
Hose Length (ft.)	50
Number of Nozzles	4





### **PRESSURE WASHER ACCESSORIES**



• PW-3100, PW-3200, PW-3600

Part#: 99944100702







#### Spray Tips (5 piece)

• PW-3100, PW-3200, PW-3600

Part#: 99944100703



#### 35 ft. Pressure Washer Hose

• PW-3100. PW-3200. PW-3600

Part#: 99944100700



#### Spray Gun

• PW-3100, PW-3200, PW-3600

Part#: 99944100701



#### **Turbo Nozzle**

• PW-3100, PW-3200, PW-3600

Part#: 99944100704



#### 5-in-1 Nozzle

• PW-3100, PW-3200, PW-3600

Part#: 99944100705





#### 2nd Story Nozzle Kit

Includes second story soap and rinse nozzle.

• PW-3100, PW-3200, PW-3600

Part#: 99944100706



#### **Quick Connect Coupler Kit**

• PW-3100, PW-3200, PW-3600

Part#: 99944100707



#### 15 in. Surface Cleaner

• PW-3100. PW-3200. PW-3600

Part#: 99944100708



#### Red Armor® Pump Guard

Great for protecting pressure washer pumps during storage as well as keeping pistons and seals fresh during the season for easy trouble-free start up.

Part#: 5555004 4 fl. oz. bottle

	PWE-1800	PW-3100	PW-3200	PW-3600	PW-4200
PRESSURE WASHERS	₽	A	A	Ā	₹
Features and Benefits					
Variable pressure spray and turbo nozzles included	•				
Uses 80% less water than a standard garden hose	•				
Convenient on-board detergent tank included	•	•			
Auto on/off pump for prolonged durability	•				
Flat-free tires for easy transport	•	•	•	•	•
Detergent Injection System			•	•	•
Reversible handles for compact storage		•	•	•	•
On-board storage for nozzles, hose and wand	•	•	•	•	•
Pro wand with auxiliary handle for comfort			•	•	
Powered by Honda GX390 engine					•
AR brand triplex pump					•
Wand, hose and nozzle quick connect coupler		•	•	•	•

### **SPECIFICATIONS**

Model`	Pressure Rating	Flow Rate	Pump	Hose Length (ft.)	Wheel Size (in.)	Unit Weight (lbs.)
PWE-1800	1800	1.3 GPM	Axial	20	5.5	30
PW-3100	3100	2.5 GPM	Axial	25	12	80
PW-3200	3200	2.5 GPM	Axial	30	10	82
PW-3600	3600	2.5 GPM	Triplex	35	10	86
PW-4200	4200	4.0 GPM	Triplex	50	12	145



ECHO's professional-grade 58V cordless line-up features six different tools that are powerful and offer gas-like performance. Whether you're a homeowner looking for battery-operated equipment or a professional who has clients that demand emission-free landscaping, ECHO's line-up delivers. All models feature brushless motor technology for less maintenance and superior performance. Each model is available as a bare tool, without a battery or charger, or is equipped with either a 2AH or 4AH battery.





With the motor mounted on the lower end, the CDST-58V is a lightweight dedicated unit for general grass trimming.

- Speed-Feed® 400 head reloads in seconds without disassembly
- 14 -16 in. adjustable cutting diameter for efficient or aggressive cutting
- High/Low speed switch for more power or extended run time
- Variable speed trigger for ultimate power control

Voltage58V
Battery 2 Amp Hour Lithium-Ion
Battery Cap 102 Watt Hours
Run Time Up to 45
Charge Time 30
Weight (lbs) 10.3
Cutting Head: Speed-Feed® 400
Cutting Swath (in.)14-16



Versatile string trimmer that works with ECHO's Pro Attachment Series™ to handle a wide variety of yard tasks.

- Accepts up to 7 additional ECHO PAS attachments for incredible versatility (see page 46 for compatibility)
- Speed-Feed® 400 head reloads in seconds without disassembly
- 14 -16 in. adjustable cutting diameter for efficient or aggressive cutting
- Variable speed trigger for ultimate power control

Voltage58V
Battery 2 Amp Hour Lithium-Ion
Battery Cap 102 Watt Hours
Run Time (min) <b>Up to 55</b>
Charge Time (min) <b>30</b>
Weight (lbs) 13.3
Cutting Head: Speed-Feed® 400
Cutting Swath (in.)14-16



### **CPLB-58V**

#### HANDHELD BLOWER



Powerful, lightweight performance for quick clean-ups at home or the job site.

- · Jet fan design for maximum clearing power
- Turbo button delivers 550 CFM for a 28% boost in air volume
- Variable speed trigger with cruise control for power control and user convenience
- Patented metal wear ring is a useful debris scraper and protects blower pipe from damage

Voltage
Newton Blowing Force (N) at nozzle13 Air volume at nozzle550
Newton Blowing Force (N) at nozzle13



Features power comparable to a gas chainsaw designed for light cutting, small tree felling and general lawn clean-up.

- · 16 in. bar and chain for large cutting capacity
- · Variable speed trigger for ultimate cutting control
- · Automatic oiler for optimum oiling and longer chain life
- · Side-access chain tensioner for easy chain adjustment

Voltage58V
Battery 4 Amp Hour Lithium-Ion
Battery Cap 102 Watt Hours
Run Time 112 cuts on 6 in. log
Charge Time (min)60
Weight (lbs)13.7
Bar Length (in.)16



Powerful, emission-free hedge trimmer delivers long run time and incredible performance.

- 24 in. double-sided, double-reciprocating blades for extended reach and cutting ability
- 3/4 in. cut capacity to handle thick branches
- · Anti-jam technology for continuous cutting
- · Heavy-duty gear case for extended durability

Voltage58V
Battery 2 Amp Hour Lithium-Ion
Battery Cap 102 Watt Hours
Run Time (min)Up to 90
Charge Time (min) <b>30</b>
Weight (lbs) 11.5
Blade Length (in.) 24





Battery-operated push mower for emission-free lawn maintenance.

- · Dual battery storage for on-board convenience
- 7-position cutting height adjustment for versatile cutting
- Heavy-duty 21 in. composite deck with lifetime guarantee
- Bag or mulch grass clippings. Side-discharge chute accessory available

Voltage58V
Battery 4 Amp Hour Lithium-Ion
Battery Cap 102 Watt Hours
Run Time (min)Up to 40
Charge Time (hr) 1
Weight (lbs)57
Cutting Width (in.)21
Cutting Height (in.) 3/4 up to 4

#### Lawn Mower Accessories

21" Mower Blade Part#: EALB-58V

Mower Bag Part#: 970687001 Side Discharge Chute Part#: ALSD-58V





#### 2AH Lithium-Ion Battery

- 30 min. recharge time
- 2.7 lbs.

Part#: CBP-58V2AH



#### **4AH Lithium-Ion Battery**

- 1 hour recharge time
- 4 lbs.

Part#: CBP-58V4AH



#### Lithium-Ion Charger

 Features innovative charging technology for battery protection

Part#: CBC-58VA



# DRILL/AUGER/CULTIVATOR





**ENGINE DRILL** 



Featuring compact power for drilling holes for pest control or lineman applications.

- All-position diaphragm carburetor, with purge pump, allows operation at any angle
- Heavy-duty gear reduction converts engine power into tough drilling torque
- · Reversible function
- Heavy-duty keyed chuck holds up to 1/2 in. drill shank

Engine CC	25.4
Weight (lbs)	.11.4
Fuel Capacity (fl. oz.)	19.6
RPM 0-650 Forward/Rev	erse
Torque (ft. lb.)	12
Gear Reduction Ratio1	7.1:1
Chuck Dia. (in.)1/2	Std.



A powerful tool for digging fence post holes, planting bulbs or trees and ice fishing.

- Designed for a wide variety of auger diameters and lengths (sold separately see page 59)
- Heavy-duty handle and frame assembly reduces vibration for greater operator comfort
- · Designed for either 1- or 2-person operation
- Drills through earth, snow and ice for year-round use

Engine CC	. 42.7
Weight (lbs)	. 21.6
Fuel Capacity (fl. oz.)	. 33.8
RPM	348
Torque (ft. lb.)	. 48.9
Gear Reduction Ratio3	0.2:1



Boasting tremendous performance from a compact package for a variety of garden tilling tasks.

- Four, 10-tooth reversible, hardened-steel tines feature a lifetime warranty and provide smooth tilling action for up to 9" wide furrows
- Worm gear-type transmission (42:1 reduction) provides incredible digging torque with dirt-churning tine rpm
- · Kickstand for easy storage
- Water resistant stop switch and throttle control located at operators fingertips

Engine CC	21.2
Weight (lbs)	21.3
Fuel Capacity (fl. oz.)	16.9
Furrow Width (in.)	9
Number of Tines	4



Tiller/Cultivator Kickstand Replacement

• TC-210

Part#: 99988800900



#### **Earth Augers**

All ECHO augers have a 7/8 in. diameter shaft opening. The 6 in., 8 in. and 10 in. augers feature a flex coil design to absorb ground shock while slowing impact between blade and rock for better handling and operation.

Diameter (in.)	Length (in.)	Weight (lbs.)	Part#
2	36	5.8	99944900150
3	36	6.5	99944900160
4	36	7.5	99944900170
6	34	12	99944900180
8	34	15	99944900190
10	34	18	99944900200

#### **Dual-Blade Ice Augers**

ECHO ice augers feature a centering ring to re-drill old holes, Unique coil technology slows the impact between blade, ice, or other debris.

Diameter (in.)	Length (in.)	Part#
8	40	99944900280
10	40	99944900290

#### **Extension Shafts**

ECHO extension shafts are compatible with 3 in. - 10 in. dia. earth augers. Not for use with 12 in. dia. or larger earth augers.

Diameter (in.)	Length (in.)	Part #
7/8	12	99944900220
7/8	18	99944900210

Earth Auger Adapter with Spring	Part #
Converts 7/8 in. to 1 in. diameter	99944900335

#### **Earth Auger Blades & Points**

Description	Part #
4 inch auger	99944900230
6 inch auger	99944900240
8 inch auger	99944900250
10 inch auger	99944900260
Auger Replacement Point	99944900270

### Ice Auger Replacement Blades & Points

Description	Part#
Replacement blade for 8 in. auger	99944900300
Replacement blade for 10 in. auger	99944900310
Ice Auger Point	99944900275



### **ENGINE DRILL ACCESSORIES**

Description	Part #
2.5 in. dia. Bulb/Plant Auger (24 in. L)	99944900011
3 in. dia. Bulb/Plant Auger (24 in. L)	99944900021
3 in. dia. Heavy-duty Auger (18 in. L)	99944900061
7 in. dia. Gallon Pot Auger (12 in. L)	99944900070
Keyless Chuck	99944900320
Keyed Chuck	99944900321

#### **SPECIFICATIONS**

Model	Engine Disp. (cc)	Gear Reduction Ratio	Drill Speed (RPM)	Torque (ft. lb.)	Chuck Diameter	Fuel Cap. (fl. oz.)	Dry Weight (lb.)
EDR-260	25.4	17.1:1	0-650 forward/reverse	12	1/2 in. standard	19.6	11.4
Model	Engine Disp. (cc)	Carburetor	Max Torque at Engine	Max Torque at Auger	Fuel Cap. (fl. oz.)	Auger RPM	Dry Weight* (lb.)
EA-410	42.7	Diaphragm w/ Purge Pump	1.62 ft/lb (2.2 Nm)	48.97 ft/lb (66.4 Nm)	33.8	348	21.6
Model	Engine Disp.	Carburetor	Fuel Cap.	Dry Weight			




ECHO's line-up of professional-grade spreaders features unrivaled performance. Each model features pro-style "T" handles for comfortable operation and metal augers to keep material from seeds, fertilizer, and herbicides to ice melt flowing. Maintenance-free gear cases and durable, over-sized hoppers help to increase productivity.





Featuring durable construction perfect for homeowners applying fertilizer, pesticide, herbicide and grass seed.

- · Holds 25,000 sq. ft. of material
- Heavy-duty agitator prevents clumping of material
- · Commercial "T-handle" frame designed for comfort
- Factory-calibrated spread pattern can be controlled with side deflector









A commercial-grade spreader with increased capacity for higher efficiency.

- Factory-calibrated spread pattern assures even, accurate coverage
- Patented auger keeps material flowing by breaking up clumps
- Maintenance-free gear case maintains proper gear mesh

A commercial-grade spreader with stainless steel frame, axles and hardware to withstand harsh conditions.

- Factory-calibrated spread pattern assures even, accurate coverage
- Patented auger keeps material flowing by breaking up clumps
- Maintenance-free gear case maintains proper gear mesh

A spreader designed exclusively for winter applications of ice melt and rock salt.

- Spiked stage agitator allows large material to flow freely through large hopper opening
- Adjustable deflectors create spread pattern from 2 8 ft. without getting into landscaped areas
- Stainless steel frame along with manual chute control closes off chute plate
- · Maintenance free heavy-duty gear case

Weight (lbs)
Hopper Height (in.) 10.73
Handle Length (in.) 32
Hopper Capacity (lbs) 80
Frame Powder-coated Steel





Weight (lbs) 40
Hopper Height (in.) 12.68
Handle Length (in.) 32
Hopper Capacity (lbs) 100
FrameStainless Steel





Weight (lbs) 43
Hopper Height (in.) 12.68
Handle Length (in.) 32
Hopper Capacity (lbs) 100
FrameStainless Steel





SPREADER

**SPREADER** 



ECHO's hand tools are the perfect complement for any yard task. Their ergonomic design will make pruning, lopping, or chopping a breeze. Quality materials like high-carbon steel or stainless steel blades and low-moisture, end-grain hickory wood handles ensure you're getting a professional-grade tool.





#### PRECISION HAND SNIPS

Precision snips for harvesting and pruning plants, herbs, stems and buds.

- · Lightweight composite handle for lightweight strength
- Stainless steel blades resist corrosion
- · Heavy-duty spring reduces hand fatigue
- · Easy-to-close blade locking clasp for right- or left-handed use

Cutting Capacity (in.).... Up to 1/2 Blade Type.....Stainless Steel Handle Grip .. Non-slip rubber grip

# **BYPASS PRUNER**



Adjustable grip bypass pruner with shock-absorbing design for more comfort while pruning.

- · Lightweight composite handle with rubber overmolded grip for comfortable control
- · Adjustable cutting range easily select large or small grip
- Low-friction coated blades provide smooth cuts when trimming and shaping
- · High carbon steel for superior blade durability

Cutting Capacity (in.)...... Up to 1 Blade Type..... High Carbon Steel Handle Grip ..... Rubber Overmold



Bypass pruner with shock-absorbing design for more comfort while pruning.

- · Lightweight composite handle with rubber overmolded grip for comfortable control
- · Gear technology increases cutting power by 3x
- · Low-friction coated blades provide smooth cuts when trimming and shaping
- High carbon steel for superior blade durability

Cutting Capacity (in.).... Up to 5/8 Blade Type..... High Carbon Steel Handle Grip ..... Rubber Overmold

#### **PRO BYPASS PRUNER**



Pro series bypass pruner with contoured design for more comfort in heavy cutting applications.

- Heavy-duty, lightweight aluminum handles
- Ergonomic design fits the shape and natural motion of hand for comfortable and extended daily use
- · Low-friction coated blades provide smooth cuts when trimming and shaping
- · High carbon steel for superior blade durability

Cutting Capacity (in.)...... Up to 1 Blade Type..... High Carbon Steel Handle Grip ..... Ergonomic

#### **ANVIL LOPPER**



- Gear technology increases cutting power by 3x
- · Low-friction coated blades prevent corrosion while providing smooth cuts
- High carbon steel for superior blade durability
- · Lightweight, long-reach, heavy-duty aluminum alloy handles

Cutting Capacity (in.)2.25
Blade Type High Carbon Content
Blade Length (in.) 3.5
Overall Length (in.) 32.5

### HA-291



#### **HEDGE SHEAR**

Hedge shear with wave blade design for precision shaping of hedges and foliage.

- · Gear technology increases cutting power by 3x
- · Low-friction coated blades prevent corrosion while providing smooth cuts
- · High carbon steel for superior blade durability
- Lightweight, long-reach, heavy-duty aluminum alloy handles

Cutting Capacity (in.)2.	25
Blade Type High Carbon Conte	nt
Blade Length (in.)	. 9
Overall Length (in.)	26

### HA-1142

Hatchet for smaller cutting applications, kindling or use in tight spaces.

- Factory-sharpened blade cutting edge is hardened and tempered for superior cutting performance
- · High carbon steel blade provides superior strength
- · Oil-rubbed finish on blade eliminates oxidation
- · Premium end-grain handle orientation for maximum strength and durability

Weight (lbs.)2
Blade Type High Carbon Content
Handle Length (in.)14
Handle Material Low-moisture Hickory

#### BYPASS LOPPER

Bypass lopper with scissors design for pruning live wood.

yn.

- Gear technology increases cutting power by 3x
- · Low-friction coated blades prevent corrosion while providing smooth cuts
- High carbon steel for superior blade durability
- · Lightweight, long-reach, heavy-duty aluminum alloy handles

Cutting Capacity (in.) 2.25
Blade Type High Carbon Content
Blade Length (in.) 3.5
Overall Length (in.)32.5

### **HA-1005**



### SPLITTING WEDGE

Splitting wedge for splitting logs for firewood.

- · Sharpened and ready for use
- · Tapered cutting edge for efficient splitting
- · Striking face is intended for driving splitting wedge
- · 60 degree bevel head maximizes force and splitting capability

\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	_
vveignt (ibs)	 5

### **HA-1282**



#### LIMBING AXE

Limbing axe for branch limbing or tree root removal where a chainsaw shouldn't be used.

- Factory-sharpened blade cutting edge is hardened and tempered for superior cutting performance
- High carbon steel blade provides superior strength
- Oil-rubbed finish on blade eliminates oxidation
- · Premium end-grain handle orientation for maximum strength and durability

Weight (lbs.)	2.25
Blade Type	. High Carbon Content
Handle Length (in.).	28
Handle Material L	ow-moisture Hickory







#### **FELLING AXE**

Felling Axe with heavier head and longer handle for felling trees or tree root removal.

- Factory-sharpened blade cutting edge is hardened and tempered for superior cutting performance
- · High carbon steel blade provides superior strength
- · Oil-rubbed finish on blade eliminates oxidation
- Premium end-grain handle orientation for maximum strength and durability

Weight (lbs.)	3.5
Blade Type	High Carbon Content
Handle Length (in.)	36
Handle Material I	_ow-moisture Hickory

## HA-1366



#### **SPLITTING MAUL**

Splitting Maul for splitting logs into firewood.

- Factory-sharpened blade cutting edge is hardened and tempered for superior cutting performance
- · High carbon steel blade provides superior strength
- Oil-rubbed finish on blade eliminates oxidation
- Premium end-grain handle orientation for maximum strength and durability

Weight (lbs.)	6
	High Carbon Content
Handle Length (in.)	36
Handle Material I	ow-moisture Hickory

# ACCESSORIES

## RED ARMOR® BLADE CLEANER AND LUBRICANT

Get rid of what's collected along your blade. Our exclusive formula reduces friction, prevents corrosion, and promotes post-trimming plant health.

Part#: 4550012 - 12 fl. oz. bottle



#### **Landscape Gloves**

Flexible nylon with form-fitting fingers and hook and loop wrist closure for a secure fit.

Part #: 103942194 (M) Part #: 103942196 (L) Part #: 103942197 (XL)



#### Vibration-reducing Landscape Gloves

Premium, padded leather palm to reduce vibration, form-fitting fingers, and hook and loop wrist closure for a secure fit.

Part #: 103942195 (M) Part #: 103942198 (L) Part #: 103942199 (XL)



#### Heavy-duty Work Gloves

Features leather palms and fingers to offer durability and protection against most elements and sharp objects.

Part #: 103942074





If you have large areas that need mowing and a traditional lawn mower is not an option, ECHO's wheeled trimmers can handle the job. They have the power to cut through dense grass and weeds with 5x the power of a handheld trimmer. The maneuverability works great in places a mower just can't go – along raised flowerbeds, retaining walls, fences and trees. Each trimmer is equipped with .155" dia. ECHO Cross-Fire® line so it will make quick work of even the thickest grass and weeds.





# *NEW* **WT-1610**

#### WHEELED TRIMMER

Designed to easily trim open spaces of long, dense grass.

- Easy-start Briggs & Stratton® OHV engine
- · Large 16 in. wheels for easy maneuverability
- · Folding ergonomic handle design
- · Removable nose piece for easy belt inspection

Engine CC 163
Weight (lbs) <b>78</b>
vveignit (ibs)
Fuel Capacity (fl. oz.)25
Trimmer Type Walk behind/push
Cutting Swath (in.)24
Standard Line Dia. (in.)





NEW

WHEELED TRIMMER ACCESSORIES



#### **Pro-line Trimmer Head**

• WT-1610, WT-1610T, WT-1610SHP

Part#: 99944400000



#### No Spark Mow Ball

• WT-1610, WT-1610T, WT-1610SHP

Part#: 99944400001



### *new* **WT-1610**T

#### WHFFI FD TRIMMFR

Built in tilt feature allows the unit to cut underneath fence lines and other barriers.

- Easy-start Briggs & Stratton® OHV engine
- · Large 16 in. wheels for easy maneuverability
- · Folding ergonomic handle design
- Tilt-n-trim feature allows the operator to efficiently cut hard to reach areas as well as around and under obstructions

Engine CC	163
Weight (lbs)	84
Fuel Capacity (fl. oz.)	25
Trimmer Type Walk behind/	push
Cutting Swath (in.)	24
Standard Line Dia. (in.)	.155





A 3-speed transmission allows easy use for cutting long, dense grass with minimal pushing effort.


- Honda® GCV engine
- · Large 16 in. wheels for easy maneuverability
- · Folding ergonomic handle design
- Self-propelled feature allows for easier maneuverability over rough terrain

Engine CC	160
Weight (lbs)	99
Fuel Capacity (fl. oz.)	30
Trimmer Type 3 speed self-pro	pelled
Cutting Swath (in.)	24
Standard Line Dia. (in.)	155





CROSS-FIRE®: MULTI-SIDED						
	50 Count		Large Clam	e Clam	Medium Spool	
Line Dia. (in.)	Length (in.)	Part #	Length (ft.)	Part #	Length (ft.)	Part #
.155	21	102225155	126	311155066	378	314155056
.175	21	102225175	75	311175067	267	314175057



Be prepared for an emergency with ECHO's FP-2126 fire pump. This property-saver uses an existing water source, like a swimming pool or a pond, and can pump water where it's needed. The oversized 5-spoke wheels allow easy movement across uneven terrain. The durable tube steel frame provides the pump and engine with maximum protection and safe operation.





# **NEW FP-2126**

#### IRF PIIMP

Protect your home and other valuables with water available on your property.

- · Complete firefighting kit with easy to transport cart
- Honda<sup>®</sup> GX200 engine
- · 2 in. high-pressure water pump
- Includes 12 ft. suction hose and 50 ft. discharge hose

Engine CC	. 196
Weight (lbs)	. 130
Fuel Capacity (fl. oz.)	. 105
Max. Pressure (PSI)	85
Max Flow (GPM)	. 126
Max. Suction Lift (ft)	26





A chipper/shredder is an extremely useful machine for reducing yard debris, like downed limbs or fallen leaves, into beneficial mulch. Two reversible chipping blades and eight reversible shredding knives quickly pulverize your yard debris into 3/4" pieces with the medium debris screen in place. Commercial landscapers can add chipping and shredding services to their customers for added value, while homeowners can save time and money by reusing the mulch to hold back weed growth and retain water around shrubs or flowers or to protect perennial plants over the winter.





# **SC-2013**

#### CHIPPER/SHREDDER

Shreds leaves, small branches and chips tree limbs and other yard waste into protective garden mulch.

- Easy-start Briggs & Stratton® OHV engine
- Flat-free tires for easy transportation
- Reversible, heat-treated chipping and shredding blades
- Includes coarse debris screen. Other discharge screens available

Engine CC	. 208
Weight (lbs)	. 195
Fuel Capacity (fl. oz.)	. 100
Chipper Capacity (in.)	3
Shredder Capacity (in.)	3/4
Shredder Blades	8





### NEW SC-3013

#### CHIPPER/SHREDDER

Mid-level engine shreds leaves, small branches and chips tree limbs and other yard waste quickly and with ease.

- Easy-start Briggs & Stratton® OHV engine
- · Flat-free tires for easy transportation
- · Reversible, heat-treated chipping and shredding blades
- Includes coarse debris screen. Other discharge screens available

Engine CC	306
Weight (lbs)	228
Fuel Capacity (fl. oz.)	100
Chipper Capacity (in.)	3
Shredder Capacity (in.)	3/4
Shredder Blades	12





# NEW **SC-4213**

#### CHIPPER/SHREDDER

Our highest powered unit gets your shredding done faster, allowing you to get mulch on the ground quickly. Shreds leaves, small branches and chips tree limbs and other yard waste.

- Easy-start Briggs & Stratton® OHV engine
- Flat-free tires for easy transportation
- · Reversible, heat-treated chipping and shredding blades
- Includes coarse debris screen. Other discharge screens available

Engine CC	420
Weight (lbs)	263
Fuel Capacity (fl. oz.)	217
Chipper Capacity (in.)	3
Shredder Capacity (in.)	3/4
Shredder Blades	12





### NEW

# CHIPPER/SHREDDER ACCESSORIES



#### **Debris Screens**

3" Fine Screen

Part#: 99944300000 - SC-3013/SC-4213

Part#: 99944300004 - SC-2013

3" Medium Screen

Part#: 99944300001 - SC-3013/SC-4213

Part#: 99944300005 - SC-2013

3" Coarse Screen

Part#: 99944300002 - SC-3013/SC-4213

Part#: 99944300006 - SC-2013

3" Wet Debris Screen

Part#: 99944300003 - SC-3013/SC-4213

Part#: 99944300007 - SC-2013



**All-Weather Cover** 

• SC-2013, SC-3013, SC-4213

Part#: 99944300008



#### **Leaf Tamper**

• SC-2013, SC-3013, SC-4213

Part#: 99944300009



#### **Two-Wheel Tow Kit**

• SC-2013, SC-3013, SC-4213

Part#: 999443000010



3 in. Discharge Debris Bag

• SC-2013, SC-3013, SC-4213

Part#: 99944300011



**Blower Attachment** 

• SC-3013, SC-4213

Part#: 99944300012



**Chipper Blade Kit** 

• SC-2013, SC-3013, SC-4213

Part#: 99944300013



#### **Shredder Knives Kit**

• SC-3013, SC-4213

Part#: 99944300014



#### **Shredder Knives Kit**

• SC-2013

Part#: 99944300015



Red Armor® is first and foremost about the user. Users who buy ECHO need to be rewarded with what they need most: Performance. The Red Armor family is designed exclusively for ECHO to deliver the ultimate performance for your outdoor power equipment. These best-in-class solutions offer a wide array of outdoor applications and continue to expand.

#### RED ARMOR® FUEL & OIL ECHO EXCLUSIVE

Red Armor® Fuel is 50:1 93 octane, ethanol-free fuel with ECHO Red Armor Oil for 2-stroke engines. Designed to deliver the ultimate performance for your engine, Red Armor Fuel cleans existing deposits, protects against future carbon build-up, and promotes longer engine life. Fuel stays fresh up to 2 years opened, 5 years unopened.

ECHO Red Armor Oil is a premium 2-stroke semi-synthetic engine oil formulated with powerful detergents and antioxidants to clean existing deposits, protect against future carbon build-up and promote longer engine life. With unique fuel stabilizers blended in, fuel stays fresh up to 2 years in a properly sealed container. JASO FD registered and ISO-L-EGD compliant. Red Armor cleans and protects to ensure optimum engine performance, and prolonged engine life.



#### RED ARMOR® FUEL

Part #: 7450001 Part #: 7450010

32 fl. oz. (6 per case) 110 fl. oz. (4 per case)

Part #: 7450005 4.75 gallons



#### **RED ARMOR® OIL**

Part #: 6550000	2.6 fl. oz. tray
Part #: 6550001	2.6 fl. oz.
Part #: 6550002	5.2 fl. oz.
Part #: 6550025	6.4 fl. oz.
Part #: 6550005	12.8 fl. oz.
Part #: 6550006	16 fl. oz.
Part #: 6550050	1 gallon
Part #: 6550250	5 gallons
Part #: 6552750	55 gallons
	1

48 loose	1 gallon mix
(8) 6 pks.	1 gallon mix
(8) 6 pks.	2 gallon mix
(8) 6 pks.	2.5 gallon mix
12 per case	5 gallon mix
12 per case	6 gallon mix
4 per case	50 gallon mix
1 pail	250 gallon mix
1 drum	2,750 gallon mix

#### RED ARMOR® FUEL TREATMENT ECHO EXCLUSIVE

Keep fuel fresh for up to two years with our unique fuel treatment. With a blend of antioxidants, detergents and an alcohol-free formula, our Red Armor Fuel Treatment works with both 2-stroke and 4-stroke engines for day-to-day use or extended storage.

Part #: 7550001 1 fl. oz. 24 piece sample pack (treats 2.5 gallons)

Part #: 7550012 12 fl. oz. bottle (6 per case)



#### NEW

#### RED ARMOR® 4-STROKE OIL ECHO EXCLUSIVE

Red Armor full-synthetic 4-stroke oil is designed to provide maximum protection under all operating conditions. SAE-5W 30. Meets API Service SP, SN Plus standards.

Part #: 6554032 32 fl. oz. bottle (12 per case)



#### NEW

#### RED ARMOR® PUMP GUARD ECHO EXCLUSIVE

Great for protecting pressure washer pumps during storage as well as keeping pistons and seals fresh during the season for easy trouble-free start up. This next generation antifreeze and lubricant will extend the life of pressure washer pumps.

Part #: 5555004 4 fl. oz. can (8 per case)



#### RED ARMOR® LUBRICANT ECHO EXCLUSIVE

This lithium-based grease is water-resistant and seals out moisture, giving you long-lasting protection. It is ideal for gear cases, spindles, cables, and ball bearings.

Part #: 94001 0.8 oz. tube (12 per case)
Part #: 94008 8 oz. tube (48 per case)
Part #: 94014 14 oz. cartridge (36 per case)
Part #: 91016 Grease gun for 8 oz. tube



#### RED ARMOR® HAND SCRUB ECHO EXCLUSIVE

Dirt-powered, water-activated, and free of harsh chemicals. Easily scrub away grease and grime!

Part #: 3550000 0.2 oz. 50 piece sample pack
Part #: 3550002 2.5 oz. tube (20 per case)
Part #: 3550008 8 oz. tube (12 per case)
Part #: 3550064 64 oz. pump bottle (2 per case)



#### RED ARMOR® BLADE CLEANER AND LUBRICANT ECHO EXCLUSIVE

Quickly boost cutting performance by getting rid of what's collected along your blades. Our exclusive formula reduces friction, prevents corrosion, and promotes post-trimming plant health.

Part #: 4550012 12 fl. oz. bottle (6 per case)



# POWER BLEND® GOLD®

Maintain fuel quality and enhance engine performance with our PowerBlend® Gold Oil.

- · For 2-stroke engines
- Semi-synthetic blend with fuel stabilizers
- · Low-smoke emissions formula
- · JASO FD registered and ISO-L-EGD compliant

Part #: 6450000G	2.6 fl. oz. tray	48 loose	1 gallon mix
Part #: 6450001G	2.6 fl. oz.	(8) 6 pks.	1 gallon mix
Part #: 6450002G	5.2 fl. oz.	(8) 6 pks.	2 gallon mix
Part #: 6450025G	6.4 fl. oz.	(8) 6 pks.	2.5 gallon mix
Part #: 6450005G	12.8 fl. oz.	12 per case	5 gallon mix
Part #: 6450006G	16 fl. oz.	12 per case	6 gallon mix
Part #: 6450050G	1 gallon	4 per case	50 gallon mix
Part #: 6450250G	5 gallons	1 pail	250 gallon mix
Part #: 6452750G	55 gallons	1 drum	2,750 gallon mix
		'	'



#### **OIL MEASURING CUP**

Part #: 6450009

4 fl. oz. capacity



#### **OIL PAIL DISPENSING PUMP**

Part #: 99909-0010

For 5 gallon pail



#### BIODEGRADABLE BAR AND CHAIN OIL

Formulated with a vegetable base, this oil is environmentally safe and designed to biodegrade over time.



1 gallon

4 per case



#### **BAR AND CHAIN OIL**

Reduce frictional heating with this unique blend of lubricants and detergents, all while lessening resin buildup and promoting chip and dust removal.

- · Anti-wear additives
- · Tackifiers for lubrication
- · 2-year shelf life when properly stored
- · Meets OECD 301 specifications

Part #: 6459012 Part #: 6459007 1 quart 1 gallon 12 per case 4 per case





By staying on top of recommended maintenance schedules, you not only prolong the life of your ECHO equipment but also save time and money by reducing large scale repairs often incurred by not properly maintaining equipment.



#### **TUNE-UP KIT**

One convenient kit with all the necessary parts to keep your ECHO equipment running at peak performance.

- Air Filter
- · Fuel Filter
- Spark Plug



#### **AIR FILTER KIT**

Fits select ECHO models.

- Air Filter
- · Lid Cleaner
- · Lid Fastener



#### **FUEL SYSTEM KIT**

One kit with all the necessary fuel components to keep your ECHO engine running smoothly.

- Fuel Filter
- Fuel Lines
- Grommet
- Fuel Gasket
- Purge Bulb

Model	Tune-Up Kit	Fuel System Kit	Gas Cap	Spark Plug	Purge Bulb	Air Filter Kit	Guide Bar Nut
Bed Redefiner BRD-2620	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
Chainsaw	001011	001021	002	001001	001001		
S-2511T*	90201Y	NA	NA	90186Y	NA	NA	NA
CS-2511T**	90196Y	NA NA	NA	90186Y	NA	NA	NA
CS-271T	90178Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-2511P	NA	NA NA	NA	90186Y	NA	NA NA	NA
S-303T	90149Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-310	90121Y	NA NA	NA	90114Y	90249Y	NA NA	90250Y
CS-3510	90200Y	NA	NA	90114Y	NA	NA NA	90250Y
S-355T***	90200Y	NA NA	NA NA	90114Y	90249Y	NA NA	90250Y
CS-355T****	90144Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-400	90155Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-4510	90197Y	NA	NA	90114Y	90249Y	NA	90250Y
CS-4910	90174Y	NA	NA	90114Y	NA	NA	90250Y
S-501P	90174Y	NA	NA	90114Y	NA	NA	90250Y
CS-590,CS-620P/PW	90167Y	NA	NA	90114Y	NA	NA	90250Y
S-7310P	NA	NA	NA	NA	NA	NA	NA
ledge Trimmer							
IC-155	90152Y	90188Y	90247Y	90114Y	90249Y	NA	NA
IC-2020	90152Y	90191Y	90247Y	90114Y	90249Y	NA	NA
IC-2210, HC-2810, HCS-2810, HCS-3810	90152Y	NA	NA	90114Y	90249Y	NA	NA
ICS-3810							
ICA-2620/S	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
SHC-225/S	90152Y	90139Y	90247Y	90114Y	90249Y	90116Y	NA
SHC-2620/S	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
Pro Attachment Series <sup>™</sup>							
AS-225/SB/VP/VPB	90152Y	90127Y	90247Y	90114Y	90249Y	90116Y	NA
AS-2620	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
Blower	004001/	00404)/	000471/	00444)/	00040\/	A I A	NIA
PB-2520	90183Y	90184Y	90247Y	90114Y	90249Y	NA	NA
PB-255LN	90154Y	90130Y	90247Y	90114Y	90249Y	NA	NA
PB-2620	90192Y	90193Y	90247Y	90114Y	90185Y	NA	NA
PB-265LN	90154Y	NA	90247Y	90114Y	90249Y	NA	NA
PB-580H/T	90156Y	90158Y	90247Y	90114Y	90249Y	NA	NA
PB-755SH/ST	90156Y	90133Y	90247Y	90114Y	90249Y	NA	NA
PB-770H/T	90122Y	NA	90247Y	90114Y	90249Y	NA	NA
PB-9010H/T	90194Y	90195Y	90247Y	90186Y	90249Y	NA	NA
dger							
PE-225	90152Y	90127Y	90247Y	90114Y	90249Y	90116Y	NA
PE-2620/S	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
Power Pruner®							
PF-225	90152Y	90139Y	90247Y	90114Y	90249Y	90116Y	NA
PF-2620, PPT-2620/H	90181Y	90182Y	90247Y	90186Y	90185Y	NA	NA
Shred 'N' Vac®							
S-250	90152Y	90129Y	90247Y	90114Y	90249Y	90112Y	NA
iller							
C-210	90152Y	90176Y	90247Y	90114Y	90249Y	90112Y	NA
rimmer/Brushcutter							
GT-225/i/L/SF, SRM-225/i/U	90152Y	90127Y	90247Y	90114Y	90249Y	90116Y	NA
RM-2320T	90198Y	90199Y	90247Y	90114Y	90249Y	NA	NA
RM-266	90125Y	90137Y	90247Y	90114Y	90249Y	NA	NA
RM-2620/T/U	90181Y	90182Y	90247Y	90186Y	90185Y	NA NA	NA NA
RM-3020/T/U	90181Y	90190Y	902471 90247Y	90186Y	90185Y	NA NA	NA
RM-410X/U	NA	NA	90247Y 90247Y	NA	901651 90249Y	NA NA	NA NA
rimmer Head Maintenance Kit	INA	IVA	302471	IVA	302431	INA	INA
or ECHOmatic Pro™ Trimmer Head				00113 Trimma	Spool		
or Echomatic Pro Trimmer Head for Speed-Feed® 400 Trimmer Head	90113 - Trimmer Spool						
	90170Y - Cap & Spring Kit / 90170YB - Cap & Spring Kit (bulk) 90189YB - Cap and Spring Kit (bulk)						

\*\*\*\*Built before 12/2020

\*Built 1/2020 & after \*\*Built before 1/2020



### PERSONAL PROTECTION ACCESSORIES

ECHO safety glasses are lightweight and impact-resistant. All models meet ANSI 787.1 standard.

Safety Glasses	Description		Part #
Tech	3	Integrated nose piece, non-slip rubber temple tips	102922451
Tiger		Suspended lenses, 5-position ratcheting temple pieces, 3-position nose width	102922455
Jet		Rubber nose piece, removable elastic headband, anti-fog coating	102922457
Turbine	8	Non-slip rubber pads on temple tips, gray tint side lenses	102922456
Pro II	63	Multi-color tinted lens with gray frame	102922460
Traveler	<b>₩</b>	Seamless curved lens, nose buds, length-adjustable temple pieces	102922453
Aviator		Anti-glare lens with anti-fog coating, 4-position ratcheting length-adjustable temple pieces	102922458

#### **Landscape Gloves**

Flexible nylon with form-fitting fingers and hook and loop wrist closure for secure fit.

Part #: 103942194 (M) Part #: 103942196 (L) Part #: 103942197 (XL)



#### Vibration-reducing **Landscape Gloves**

Premium, padded leather palm to reduce vibration, form-fitting fingers, and hook and loop wrist closure for secure fit.

Part #: 103942195 (M) Part #: 103942198 (L) Part #: 103942199 (XL)



#### **Heavy-duty Work Gloves**

Features leather palms and fingers to offer durability and protection against most elements and sharp objects.

Part #: 103942074



#### **Safety Shirts**

Designed with moisture-wicking material for breathability and comfort to keep you cool. Reflective striping detail and high-visibility color ensures you're seen at all times. Meets ANSI/SEA 107-2010 Class 2 standards. Available in both long and short sleeves.

Part #: 99988801809 Short Sleeve (M) Part #: 99988801810 Short Sleeve (L) Part #: 99988801811 Short Sleeve (XL) Part #: 99988801812 Short Sleeve (XXL) Part #: 99988801813 Long Sleeve (M) Part #: 99988801814 Long Sleeve (L) Part #: 99988801815 Long Sleeve (XL) Part #: 99988801816 Long Sleeve (XXL)



#### **Safety Vests**

Highly-visible vest features 5-point tear-away panels for safety.

Part #: 99988801400 (L) Part #: 99988801401 (XL) Part #: 99988801402 (XXL)



#### **Hearing Protection**

Helps reduce potentially harmful noise emissions from damaging hearing. NRR 29 dB(A) rating. Meets ANSI S3.19 standards.

Part #: 99988801520



#### **Brushcutter System**

Includes steel mesh face visor and ear muffs offering excellent face and ear protection while trimming or brushcutting. NRR 24 dB(A) rating.

Part #: 99988801510



#### **Equipment Bag**


Carryall solution for work gear and/or extra accessories to keep

everything in one place.

Dimensions: 24 in. L x 12 in. H x 11 in. W

Part #: 103942145





#### **Earplugs with Case**

ANSI and OSHA approved. Carrying case keeps earplugs clean and ready to go. NRR 23 dB(A) rating.



Part #: 103942210

### Premium Brushcutter Harness

Featuring 4-point suspension system enabling easier handling and reduces weight-bearing. Padded shoulder straps for comfort with quick-release pin for safety. Max waist size: 40 in.

Part #: 99944200202



#### **Shin Guards**

Light weight with padded shins and hook and loop straps for easy on/off access. Water resistant.

- Fits up to 23 in. calf circumference
- Dimensions: 18 in. H x 9 in. W

Part #: 103942180



#### **Boshi™ Convertible Scarf**

Provides relief from harsh outdoor conditions such as sun, dust and heat.

Part #: 99988801000



#### **Cooling Towel**

Keeps you cool for hours. 3-layer construction absorbs sweat, stores moisture to keep you cool, and evaporates to diffuse heat.

Part #: 99988801001

#### **Shoulder Straps**

A shoulder strap helps to support the weight of a trimmer or brushcutter. Fits up to 46 in. waist. Cross-body fit: 52 in.

Part #: 99944200200 (SRM Models)
\*Use SRM strap for GT-225L

Part #: 99944200201 (GT Models)

#### **Reusable Dust Mask**

Reusable and washable with breathable mesh for cooler comfort. Provides 95% filtration.

Part #: 99988803000

Replacement Filters

Part #: 99988803005 (5 Pack)





•	www.facebook.com/ECHOUSA	
<b>©</b>	www.instagram.com/ECHOUSA	
You Tube	www.youtube.com/ECHOUSA	

ECHO Incorporated • 400 Oakwood Road, Lake Zurich, IL 60047-1564 • ECHO-USA.COM For customer service or for your nearest ECHO dealer call toll free 1-800-432-3246. In Canada, call toll-free 1-800-700-1358.

Specifications, descriptions, and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories and may not include all standard equipment.